



## M-220 M-240 M-260

Modern unique high-technology Italian style welded inflatable buoyancy tube with three hermetically-separated chambers

Inflatable keel providing correct 'V' shape in hull

Continuous 12 mm-thick marine-ply floor

Extremely rugged integral transom for outboard motor with fitted plastic plate for mounting motor

Full outboard protection guards against scuffing and keeps inside of boat dry

Drain plug in transom

Safety grab-ropes on tubes

Handle in nose also serves as towing ring

Twin towing rings

Twin rear moulded handles for lifting boat

Removable marine-ply seats, 20 mm thick, with positive, safe location; (A-220 and A-240 have single seat other Arta models have two seats)

Two oars with rowlocks, and twin tube-mounted oar supports

Lifting ring in nose of boat

Superb carrying and storage bag

Foot-pump with valve adaptor

Emergency repair kit in plastic container, including material and adhesive Operation manual









Technical information	M-220	M-240	M-260
Overall Length, (Cm)	220	240	260
Overall Width, (Cm)	145	145	145
Diameter Of Buoyancy Tubes, (Cm)	39	39	39
Quantity Of Airtight Compartments, (Pcs.)	3+1+A	3+1+A	3+1+A
Carrying Capacity: Max., (Kg)	250	280	330
Number Of Passengers: Max., (Pers.)	2	2	3
Engine Power: Max., (HP)	3.3	4	5
Engine Weight: Max., (Kg)	22	26	30
Weight Of Packed Boat, (Kg)	27	33	36
Dimensions of Pack, (Cm)	90x35x35	100x40x40	100x45x40
CE Category	-	-	D