



S-250T



S-250

SCOUT S-250 & S-250T

Welded inflatable buoyancy tube with two hermetically-separated chambers

Slatted marine-ply floorboards

Removable transom for outboard engine

Two removable wooden seats

Two oars with oarlocks, and twin tube-mounted oar supports

Safety grab-ropes on tubes

Bow towing ring, and rear ring for anchor rope

Superb rucksack for carrying and storage of the boat and accessories

Foot-pump with valve adaptor

Emergency repair kit in plastic container, including material and adhesive

Operation manual



| Technical information | S-250 | S-250T |
|---|----------|----------|
| Overall Length, (Cm) | 250 | 250 |
| Overall Width, (Cm) | 120 | 120 |
| Diameter Of Buoyancy Tubes, (Cm) | 34 | 34 |
| Quantity Of Airtight Compartments, (Pcs.) | 2 | 2 |
| Carrying Capacity: Max., (Kg) | 220 | 220 |
| Number Of Passengers: Max., (Pers.) | 2 | 2 |
| Engine Power: Max., (HP) | - | 2 |
| Engine Weight: Max., (Kg) | - | 14 |
| Weight Of Packed Boat, (Kg) | 16 | 17 |
| Dimensions of Pack, (Cm) | 90x40x33 | 95x40x33 |
| CE Category | - | - |