



T-200



T-220

T-200 T-220 T-240 T-260 T-290

Welded inflatable buoyancy tube of classic design, with two hermetically-separated chambers

Slatted marine-ply floorboards

Integral transom for outboard motor with plastic mounting plate

Full outboard guards against scuffing, and keeps inside of boat dry

Drain plug in transom

Removable wooden seats; (T-220 and T-240 have one seat other models have two seats)

Two oars with rowlocks, and twin tube-mounted oar supports

Safety grab-ropes on tubes

Bow towing ring

Superb boat storage bag contains further bag containing seat(s) and floorboards

Foot-pump with valve adaptor

Emergency repair kit in plastic container, including material and adhesive
Operation manual



Technical information

	T-200	T-220	T-240	T-260	T-290
Overall Length, (Cm)	200	220	240	260	290
Overall Width, (Cm)	142	142	142	142	145
Diameter Of Buoyancy Tubes, (Cm)	38	38	38	38	38
Quantity Of Airtight Compartments, (Pcs.)	2	2	2	2	2
Carrying Capacity: Max., (Kg)	200	220	250	300	330
Number Of Passengers: Max., (Pers.)	2	2	3	3	4
Engine Power: Max., (HP)	3,3	3,3	4	5	6
Engine Weight: Max., (Kg)	22	22	26	30	38
Weight Of Packed Boat, (Kg)	16	18	26	32	36
Dimensions of Pack, (Cm)	85x45x35	85x45x35	85x45x40	85x50x45	85x55x45
CE Category	-	-	D	D	D