Adventure





T-220K T-240K T-260K

- Welded inflatable buoyancy tube of classic design, with two hermeticallyseparated chambers
- Inflatable keel providing correct 'V' shape in hull
- Continuous 12 mm-thick marine-ply floor

Precision anodised-aluminium extruded sections enabling perfect jointing of floor sections

Extremely rugged integral transom for outboard motor with fitted plastic plate for mounting motor

Full outboard protection guards against scuffing, keeps inside of boat dry Drain plug in transom

Safety grab-ropes on tubes

Handle in nose also serves as towing ring

Twin towing rings

Twin rear moulded handles for lifting boat

Two removable marine-ply seats, 15 mm thick, with positive, safe location Two oars with rowlocks, and twin tube-mounted oar supports Superb carrying and storage bag;

(secondary bag for seats and floorboards fits inside main bag) Foot pump with valve adaptor

Emergency repair kit in plastic container, including material and adhesive Operation manual





Technical information	Т-220К	T-240K	Т-260К
Overall Length, (Cm)	220	240	260
Overall Width, (Cm)	142	142	142
Diameter Of Buoyancy Tubes, (Cm)	38	38	38
Quantity Of Airtight Compartments, (Pcs.)	2+1	2+1	2+1
Carrying Capacity: Max., (Kg)	220	300	330
Number Of Passengers: Max., (Pers.)	2	2	3
Engine Power: Max., (HP)	3,3	4	5
Engine Weight: Max., (Kg)	22	26	30
Weight Of Packed Boat, (Kg)	26	30	38
Dimensions of Pack, (Cm)	85x60x35	85x65x35	90x73x38
CE Category	-	D	D