

T-290K T-300K T-320K




T-290K



T-320K

Welded inflatable buoyancy tube of classic design, with two hermetically-separated chambers
 Inflatable keel providing correct 'V' shape in hull
 Continuous 12 mm-thick marine-ply floor
 Precision anodised-aluminium extruded sections enabling perfect jointing of floor sections
 Extremely rugged integral transom for outboard motor with fitted plastic plate for mounting motor
 Full outboard protection guards against scuffing, keeps inside of boat dry
 Drain plug in transom
 Safety grab-ropes on tubes
 Handle in nose also serves as towing ring
 Twin towing rings
 Twin rear moulded handles for lifting boat
 Two removable marine-ply seats, 15 mm thick, with positive, safe location
 Two oars with rowlocks, and twin tube-mounted oar supports
 Superb carrying and storage bag;
 (secondary bag for seats and floorboards fits inside main bag)
 Foot pump with valve adaptor
 Emergency repair kit in plastic container, including material and adhesive
 Operation manual



Technical information	T-290K	T-300K	T-320K
Overall Length, (Cm)	290	300	320
Overall Width, (Cm)	145	145	145
Diameter Of Buoyancy Tubes, (Cm)	38	38	38
Quantity Of Airtight Compartments, (Pcs.)	2+1	2+1	2+1
Carrying Capacity: Max., (Kg)	380	450	450
Number Of Passengers: Max., (Pers.)	4	4	4
Engine Power: Max., (HP)	8	15	15
Engine Weight: Max., (Kg)	38	45	45
Weight Of Packed Boat, (Kg)	42	46	46
Dimensions of Pack, (Cm)	100x60x40	105x65x40	105x65x40
CE Category	D	D	D