



Bestellnummer 6232 (S2)

MADE IN AUSTRIA

Bezeichnung ASPHALTPROFI HS S2
Norm EN ISO 20345:2011, S2 HI-CI-HRO, Form A
ÖNORM Z 1259:2017/DGUV 112-191

FEATURES



**UP TO ONE HOUR ON
HOT SURFACE!**

DESCRIPTION

Upper leather:	water, oil and dirt resistant genuine leather in special quality, thickness approx. 2.1 mm
Lining:	high absorbing, natural & perforated orthopedic leather lining, thickness from 1.0 - 1.4 mm
Toe cap:	High, wide FreeToes safety steel toe cap with flexible transition lip
Cushion	Replaceable cushion inlay with spherical heel and distinct arch support
Insole:	Genuine leather, vegetable tanned, thickness from 2.4 to 2.7 mm, removable anatomically shaped, moisture-regulating, breathable, antibacterial & washable
Sole:	DUO-SOFT-ASPHALT Sole (Rubber-PUR) SEALING SOLE EDGE SYSTEM Patent No. 403677 Nitrile rubber mole (slip resistant, microbe and acid resistant, fuel & oil resistant) Polyurethane foam body (lightweight, shock absorbent, permanently elastic) highly insulated with warmth and heat resistant special fibre fabric Heat and cold insulated according to EN ISO 2034:2012 (HI-CI) Contact heat resistant up to 572°F according to ÖNORM EN ISO 20345:2012 (HRO)
Sizes:	7.0 - 13.0 (USA size) 40 - 48