



Ordernumber **6432** (S2)

MADE IN AUSTRIA

Model **ASPHALTPROFI KH S2**  
Norm EN ISO 20345:2011, S2 HI-CI-HRO, Form B  
ÖNORM Z 1259:2017/DGUV 112-191

## FEATURES



**UP TO ONE HOUR ON  
HOT SURFACE!**

## DESCRIPTION

<b>Upper leather:</b>	water, oil and dirt resistant genuine leather in special quality, thickness approx. 2.1 mm
<b>Lining:</b>	high absorbing, natural & perforated orthopedic leather lining, thickness from 1.0 - 1.4 mm
<b>Toe cap:</b>	High, wide FreeToes safety steel toe cap with flexible transition lip
<b>Cushion</b>	Replaceable cushion inlay with spherical heel and distinct arch support
<b>Insole:</b>	Genuine leather, vegetable tanned, thickness from 2.4 to 2.7 mm, removable anatomically shaped, moisture-regulating, breathable, antibacterial & washable
<b>Sole:</b>	DUO-SOFT-ASPHALT Sole (Rubber-PUR) SEALING SOLE EDGE SYSTEM Patent No. 403677 Nitrile rubber mole (slip resistant, microbe and acid resistant, fuel & oil resistant) Polyurethane foam body (lightweight, shock absorbent, permanently elastic) highly insulated with warmth and heat resistant special fibre fabric Heat and cold insulated according to EN ISO 2034:2012 (HI-CI) Contact heat resistant up to 572°F according to ÖNORM EN ISO 20345:2012 (HRO)
<b>Sizes:</b>	7.0 - 13.0 (USA size) 40 - 48