

# FASHION 3D LEATHER COLLECTION™

## THE 3D PATTERNED HEAT TRANSFER FILM COLLECTION ALLOWING A REALISTIC LEATHER PERSONALISATION EFFECT

Looking for a realistic leather effect on your accessories? Fashion 3D leather is a PU that will bring great and deep leather effect, with relief texture.

### Fashion accessories



### Product description

- ✓ Leather effect is a classic fashion MUST-HAVE to bring your personalisation to another level! It never goes out of style.
- ✓ 3D effect texture.
- ✓ Glossy finish.
- ✓ Discover the colour of our leather collection:



Brown leather 660

### Application key points

- ✓ Easy to cut.
- ✓ Very easy to weed! → Save production time.
- ✓ Thanks to its adhesive backing, the design can be repositioned after weeding.

### Usage benefits

- ✓ Agreeable to touch thanks to its 3D texture.
- ✓ Highly recommended for fashion accessories.
- ✓ Easy to care → Can be washed up to 60°C.

## SPECIFICATIONS

Composition	Average Thickness	Carrier	Dimensions
PU	170 µm	Adhesive & Transparent Polyester	50 cm x 5 m

## APPLICATION INSTRUCTIONS

Applies on	Cutting	Application Temp. & Duration
Cotton Polyester Acrylic Cotton/Polyester blend without repellent treatment	Use a Flex Blade 45°	160°C – 20 s 320°F – 20 s

Pressure	Peeling
Medium	Cold

### Step 1 – Cutting

Cut your design in mirror with a standard flex blade (45°).

### Step 2 – Weeding

Remove the excess of material (easy weeding).

### Step 3 – Application

Position your design on the textile and press it with a Sefa DUPLEX/ROTEX, or equivalent, at 160°C/320°F for 20 seconds, with a medium pressure.

We do recommend the use of a silicone paper to protect the designs and the textile during the application.

### Step 4 – Peeling

Peel the material when cold.

*NOTE: We highly recommend you to perform tests before launching a production.*

## CARE AND MAINTENANCE RECOMMENDATIONS

Washing	Ironing	Tumbledry	Dry cleaning
Up to 60°C/140°F	On reverse only	Yes	Not recommended

### Care and maintenance:

- ✓ Always respect the garment instructions.
- ✓ Wait 24 hours after the application before the first wash.
- ✓ Avoid the use of aggressive products.

Storage life	Storage Temperature	Storage Lighting	Position
Up to 1 year	Dry room with 15-30°C/59°F-86°F	Away from sunlight	Vertical position

### Washing recommendations:

- ✓ Respect the textile recommendations.
- ✓ Preferably inside out to extend the design's life.
- ✓ Do not bleach.