COMPACTTILT™

CT1

Tilt for mini excavators

Up to 1.200 kg



ONLY 20 KG - LOWEST PRODUCT WEIGHT ON THE MARKET
160 MM INSTALLATION HEIGHT AND 2×50° TILT ANGLE
COMPACT DESIGN FOR WORKING IN NARROW TRENCHES

Compacttilt™ CT1 is developed for mini excavators, where low weight, compact design and maximum flexibility are essential. With an installation height of just 160 mm and a total tilt angle of 100°, you get greater flexibility and precision – even in confined spaces.

With a width of just 148 mm, the CT1 is designed for working in narrow trenches and confined areas. Its cylinder-free design means that no components protrude beyond the machine's mounting interface, while its low weight helps preserve the mini excavator's lifting capacity.

The CT1 is equipped with CT-LOCK™ and can be configured with either a semi-automatic or hydraulic quick coupler with three hoses. This gives you a compact and flexible solution tailored to your machine and working requirements.

CT1 FACTS

- **20 kg own weight** - lowest product weight on the market, according to Compacttilt
- **160 mm installation height** - compact mounting on the mini excavator
- **100° total tilt angle** - 2x50° for flexible excavation work
- **Only 148 mm wide** - designed for narrow trenches and 200 mm buckets
- **Cylinder-free design** - no protruding side cylinders
- **CT-LOCK™** - double locking safety system according to EN 474-5
- **Two quick coupler options** - semi-automatic or hydraulic with 3 hoses
- **Designed and manufactured in Denmark** - compact technology for professional excavation work



20 KG
OWN WEIGHT

160 MM
INSTALLATION HEIGHT

2×50° TILT
100° TOTAL TILT ANGLE

148 MM
WIDTH

CT-LOCK™
ACCORDING TO 474-5

2
QUICK COUPLER OPTIONS

DANISH
DESIGNED AND MANUFACTURED