COMPACTTILT™

COMPACT DESIGN. POWERFUL PERFORMANCE.

Compacttilt™ is the most compact tilt on the market, with an installation height up to **40% lower** than alternatives. The low installation height allows you to dig a sharp edge close to the machine. **Compacttilt™** offers a tilt angle of **2x50°**, enabling versatile operation. **Compacttilt™** can be equipped with a valve system and valve block for easy and efficient installation on the machine.

No cylinders
No cylinders beyond the machine mounting, allowing the machine to work even in confined spaces.

Unique low weight
The uniquely low weight allows the machine to retain its pulling force and the bucket to be fully utilised.

The most compact tilt on the market
The most compact tilt on the market, with an installation height up to 40% lower than alternatives. The low installation height allows you to dig a sharp edge close to the machine.



Protective shielding
Protective shielding for all exposed components, with no protruding parts beyond the machine mounting.

Quick coupler
Hydraulic quick coupler and pin-lock system as standard.

Greater tilt angle
The full 100° tilt angle (2x50°) enables versatile operation.

Valve system
Can be equipped with a valve system and valve block for easy and efficient installation on the machine.

CT-Lock
Double locking safety
Enhances safety and provides extra peace of mind in everyday operation. The system is designed for high operational reliability and in accordance with the requirements of EN 474-5.

CT2 (Max 2,2T)



Installation height
from 170 mm
Width
148mm
Weight
30 kg

CT3 (Max 3T)



Installation height
from 200mm
Width
198mm
Weight
38 kg

CT6 (Max 6T)



Installation height
from 235mm
Width
198mm
Weight
65 kg

CT10 (Max 10T)



Installation height
from 250mm
Width
288mm
Weight
95 kg

COMPACTTILT™

TECHNICAL SPECIFICATIONS

Explore the technical specifications of **Compacttilt™** and find the model that suits your machine and application.

Model	 CT2 (Max 2T)	 CT3 (Max 3T)	 CT6 (Max 6T)	 CT10 (Max 10T)
Recommended max. machine weight [T]	2,2	3	6	10
Installation height from [mm]	170	200	235	250
Width [mm]	148	198	198	288
Length [mm]	200	313	302	372
Weight incl. quick coupler and machine mounting [kg]	30	36	65	95
Total rotation angle	100°	100°	100°	100°
Tilt angle	2x50°	2x50°	2x50°	2x50°
Max. hydraulic pressure [MPa]	250	250	250	250
Hydraulic flow [L/min]	2-4	3-6	4-12	6-14
Pin-lock opening/closing force [kN]	0,6	1	1	1
Quick coupler type	S30-150, S30-180, MH30	S40, CW05, HS03	S40, CW05, CW10, Hydreama, S45	CW10, Hydrema, S45

Note: Specifications are indicative and may vary depending on machine type, equipment and configuration.

BUILT FOR THE REAL WORLD

Compacttilt™ is developed for professionals who need maximum flexibility, reliability and efficiency every day.





