



ABARTH



ABARTH 500 TECHNICAL SPECIFICATION SHEET

ENGINE

- 4 cylinders in line, 4 valves per cylinder, 1368 cc
- Power output: 135 bhp (99 kW) at 5,500 rpm
- Max torque in SPORT mode 206Nm at 3,000rpm
- Drive-by-wire accelerator controls with no mechanical connection
- Turbocharged by IHI turbocharger
- CO2 emissions: 155g/km
- Fuel Cons (mpg (l/100km)):
urban 33.2 (8.5) / extra-urban 43.5 (6.5) / combined 52.3 (5.4)

TRANSMISSION

- 5-speed gearbox • Dual cable external gearbox control

SUSPENSION AND STEERING

- MacPherson layout at front with anti-roll bar
- Interconnected wheels at rear with torsion beam and anti-roll bar
- Lowered and stiffened suspension
- Dualdrive electric power steering with SPORT mode

BRAKES

- Floating ZPH 4.1.2 front calliper, piston diameter 54 mm
- Ventilated front brake discs, diameter 284 x 22 mm
- Floating CII 34 rear calliper, piston diameter 34 mm
- Solid rear brake discs, diameter 240 x 11 mm

WHEELS

- Standard: Aluminium alloy rim 6.5" x 16" - Tyres: 195/45 R16
- Optional: Aluminium alloy rim 7.5" x 17" - Tyres: 205/40 R17

PERFORMANCE

- 0-100km/h (62mph): 7.9 seconds
- Maximum speed: 127mph

