

PEARL PREMIUM NEW



2,0 kW

2,5 kW


3,5 kW

5,0 kW

7,1 kW



Standard YR-HE + YR-HE2



- Low noise level
- Self-Clean (Only Dual)
- Integrated Wi-Fi control
- UVC Sterilisation
- Easy installation
- Coanda plus airflow



INDOOR UNIT	Model		AS20PBAHRA	AS25PBPBRA-PRE	AS35PBPBRA-PRE	AS50PDPBRA-PRE	AS71PEPBRA-PRE
Performance data							
Output power - COOLING	nom (min-max)	kW	2	2,7 (0,8-3,6)	3,6 (0,8-4,0)	5,0 (2,0-6,3)	7,1 (2,1 - 8,0)
Output power - HEATING	nom (min-max)	kW	2,5	3,1 (0,8-4,3)	3,9 (0,8-4,5)	5,8 (1,35-6,8)	7,4 (1,5-8,5)
Power supply		Ph/V/Hz	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50	1/220-240/50
Interconnection cable			4 x 1,0	4 x 1,0	4 x 1,0	4 x 1,0	4 x 1,0
Treated air volume	H	m ³ /h	550	550	640	830	910
Indoor Unit							
High sound power - COOLING		dB	54	56	60	60	65
High sound power - HEATING		dB	54	56	60	60	65
Sound pressure - COOLING		dB(A)	37/32/28/18	37/32/28/18	38/33/29/18	44/40/35/28	48/42/35/27
Sound pressure - HEATING		dB(A)	37/32/28/18	37/32/28/18	38/33/29/18	44/40/35/28	48/42/35/27
Net dimensions	WxDxH	mm	805x200x290	805x200x292	805x200x292	975x220x320	1105x240x335
Packaging dimensions	WxDxH	mm	874x270x363	874x272x365	874x272x365	1090x316x413	1185x428x331
Net/gross weight		kg	8,3/10,5	8,1/10,3	8,6/10,8	11,6/14,4	15,4/18,9
Installation data							
Liquid pipe	∅	mm	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)
Gas pipe	∅	mm	9,52 (3/8)	9,52 (3/8)	9,52 (3/8)	12,70 (1/2)	15,88 (5/8)
Control							
Standard	Remote control		YR-HE	YR-HE2	YR-HE2	YR-HE2	YR-HE2

AS20 - AS25 - AS35

AS50 - AS71

