



SCIZOR 35 FI-SUV

ELECTRO HYDRAULIC DOUBLE SCISSOR LIFT WITH SUV KIT



- Adjustable platform length
- Hydraulic Cylinders with excellent finish and connectivity made of high rotation speed CNC.
- High quality Japanese oil seals for longer life.
- Laser cut finish for high standard finish and looks.
- Solid steel structure for durability and rust resistance.

- Mechanical safety locks to ensure higher safety.
- Hydraulic synchronisation between platforms to ensure stability and balance between platforms.
- High quality Wear-resisting bearings and polymer sliders for higher durability.

· Powder coated surface finish. **SAFETY FEATURES**

2060 1660 1460 2 56 880 565 330 270mm deen 2100 PVC tubing is used for the oil pipe, trachea and wires connection of foundation pit and console vertical to the The distance between the pit and the console is 1.2-1.8 meters. The exit of the PVC tubing can be put on the right side or left side of the pit. 340mm Depth 1 70mm height above the botton Car move in. 100PVC tubing cross through two pits, 850mm long 1 70mm height above the bottom Suggested3000mm The thickness of concrete at the bottom of the pit should more than 150mm,

TECHINICAL DETAILS

	Model	Туре	Capacity	Maximum Rise	Platfrom Length	Platform Width	Motor Power	Air Pressure
Ţ	SCIZOR 35 FI - SUV	Flush/Inground Installation	3500 kgs	1999 mm	1660 -2060 mm	565 mm	3.0kw - 380v,3ph,50hz	4 - 6 bar