



LOGISTAR 100

TECHNICAL SPECIFICATIONS*

LIGHT ELECTRIC COMMERCIAL VEHICLE

The compact city runabout within the Logistar series. The new Logistar 100 - made for fast deliveries and services in the city. The new LS 100 is comparable in size to the SEAT Mii, Renault Twingo, ...

- VARIABLE APPLICATION AREAS
 Express delivery, postal services, delivery services, facility management, care services
- PAYLOAD AND LOAD CAPACITY
 525 kg payload and 2 m³ load capacity
- VEHICLE CLASSIFICATION N1
- CHARGING AND RANGE

Charging time: 5h (230 V), up to 162 km at full charge (WLTP City)



Central locking, Reversing Camera, Electric Power Steering (EPS), E-Call, Multimedia system, electric windows, air conditioning, tire pressure monitoring, Antilock Braking System (ABS), Power brakes

BASIC INFORMATION

Vehicle Size (L x W x H)	3664 x 1610 x 1689 mm
Wheel Base	2485 mm
Track width front / rear	1360 / 1355 mm
Cargo Volume	2 m ³
Max. Laden Mass	1520 kg
Curb Weight**	995 kg
Payload	525 kg
Tyre size	175/60 R14 79H



525 kg payload

 $2 \, \text{m}^3$

N1

^{*} Technical as well as equipment changes are reserved. All information on Cenntro products corresponds to the status on the day of publication. Errors and mistakes cannot be totally excluded.

^{**} Incl. Battery and Driver (75kg).



CENNTRO

LOGISTAR 100

TECHNICAL SPECIFICATIONS & EQUIPMENT*

PERFORMANCE

Speed max.	80 km/h
Max. Range WLTP	118 km / 162 km
(combined/city)	
Consumption combined	15 KWh/100 km
Rated/Peak Power	12/25 KW
Peak Torque	90 Nm



ELECTRIC SYSTEM

Battery Type	LiFePO4 (16 kWh)
AC charging capacity	max. 3,3 kW
Charging method	Slow charge in 5 hours
Electric Motor Type	Permanent Magnet Synchronous
Drive	Front



FOLLOW US









^{*} Technical as well as equipment changes are reserved. All information on Cenntro products corresponds to the status on the day of publication. Errors and mistakes cannot be totally excluded.