



CENNTRO

LOGISTAR 260

TECHNICAL SPECIFICATION & EQUIPMENT*

ELECTRIC COMMERCIAL VAN WITH ALUMINUM BODY

The Logistar 260 is an electric commercial vehicle positioned between the so-called “Transporter” class and the “Sprinter” class. It combines the best of both worlds: Larger load volume than most vehicles in the Transporter-class and less wide than Transporter- and Sprinter-class (10-20 cm).

- **VARIABLE APPLICATIONS**

Delivery Services, CEP Service, Craftsmen, Facility Management, Rentals

- **LOAD CAPACITY**

1280 kg payload and 7,5 m³ load capacity

- **VEHICLE CLASSIFICATION**

N1

- **FAST CHARGE AND LONG RANGE**

Fast charge (DC) 30-80% in 30 min, up to 270 km range

- **HIGHLIGHT FEATURES**

Reversing alarm, Radio + USB + Bluetooth®, Antilock Braking System (ABS), Electronic Brakeforce Distribution (EBD), LED Headlights, Parc Distance Control (PDC), Reverse camera, Electric Power Steering (EPS), Air condition, Central locking, Rear doors 270° opening

• 1280 kg Nutzlast
• 7,5 m³
• Aluminium Karosserie

BASIC INFORMATION

Vehicle Size (L x W x H)	5457 x 1850 x 2046 mm
Wheelbase	3380 mm
Cargo Volume	7,5 m ³
Permissible total weight	3060 kg
Curb Weight incl. Battery and Driver	1650 kg
Payload**	1280 kg



* Technical as well as equipment changes are reserved. All information on Cenntro products corresponds to the status on the day of publication. Errors and mistakes cannot be totally excluded.

** incl. driver (75 kg)



LOGISTAR 260

TECHNICAL SPECIFICATION & EQUIPMENT*

PERFORMANCE

Max. Speed	80 km/h
Grade Ability	25 %
Max. Range WLTP combined	270 km
Consumption combined	13,5 kWh/100 km
Peak Torque	265 Nm
Rated/Peak power	40 / 75 kW

ELECTRIC SYSTEM

Battery Type	LiFePO4 (43,5 kWh)
AC charging capacity	max. 3,5 kW, 0-100%; <8h
DC charging capacity	max. 36 kW, 30-80%; 45 min
Drive	Rear



FOLLOW US

