

CV. DIAN PERSADA ROTARINDO BUILDING

HEAD OFFICE: JL. SUNAN AMPEL 102, KOTA PASURUAN-JAWA TIMUR FACTORY: JL RAYA TRAWAS KM 3.4 DESA WONOKERTO KEC, PUNGGING KAB, MOJOKERTO-JAWA TIMUR



+62 819-9830-0140 (RIZA)



+62 856-5518-8324 (NAVI)



minfo@prabottindo.com

Furniture, Wood Working Product & Molding



CV. Dian Persada Rotarindo Building is a Furniture (Rattan, wood) and wood processing industry with an export orientation that was founded in 2014, located in Pasuruan Regency (unit 1) and Mojokerto Regency (Unit 2), East Java, Indonesia. Equipped with a Timber Legality and Verification System Certification (SVLK) which states that our raw materials come from legal wood.

This SVLK shows our commitment to produce quality products as well as our commitment to environmental sustainability. We produce all types of furniture from rattan and wood and process several types of wood according to the specifications requested by buyers among the types of wood we produce as follows: Acacia Mangium (Acacia Mangium), Mahoni, Merbau, Meranti, Sengon, Duren, Bayur, Jabon etc. production 3000 m3 per year.

Furniture Products













The products we process from natural Indonesian wood products become finished products of standard export quality which have the essence of art and high natural characteristics. We produce with a strict production system and high precision to produce quality products for our customers.





Wood Working Product & Molding











The products we process are from natural Indonesian wood products such as: Akasia Mangium (Acacia Mangium), Mahoni, Merbau, Meranti, Sengon, Duren, Bayur, Jabon etc., with a strict and high-precision production system supported by the best machine facilities we have to produce quality products according to the standard grade and specifications requested by the buyer.



Production Process

SORTING



The sorting process is the selection of raw materials (rattan for furniture) and sawn wood (sawn wood), including the period of trees ready for cutting (Old Wood) and wood defects free so that it can produce high quality products. Sorted by our quality control team.

KILN DRYING



Timber that has been sorted and neatly sticked, will be put into the Kiln Dry Chamber to be dried so that it reaches a moisture content of 8-12%. With

With a standard moisture content of 8-12%, wood can be categorized as dry, hard, stable in terms of expansion and shrinkage, and termite-resistant.

MOULDING, PRODUCTION



Wood products are given a Tongue / Groove profile with a high degree of accuracy by an SNI standard machine. Quality Control conducts a final inspection to ensure that the product meets the standards

FINISHING AND QUALITY CHECKING



Rattan products after carrying out several quality checks at the start of production will undergo a scrubbing process to smooth the surface, after which the color process will be carried out according to the buyer's request. Quality checks will be carried out again by the buyer before the packing process, this is done so that our quality standards are maintained.

PACKING



Our products are packed according to the standards specified by the buyer, to avoid damage when delivering the product to the destination.

SHIPMENT



We are ready to guarantee product quality

Vision and Mission



- Achieving buyer satisfaction is our priority, with nonstop empowerment to prioritize the main interests of our customers, our employees try to serve enthusiastically.
- We are committed to producing and processing high quality products by purchasing legally certified and good quality raw materials so as to create quality products according to the standards set by our buyers.

Overview of Our Products

FURNITURE

RATTAN DPRB





VARIOUS CHAIRS





SCREEN/BLOCK






BASKET



AND VARIOUS OTHER CRAFTS

WOOD WORKING & MOULDING





E2E PRODUCT DETAILS: R2, MC UNDER 13% GRADE
A, 20–23 MM THICK, INSECT RESISTANT



FINGER JOINT STICK PRODUCT DETAILS : S4S, GRADE B/C, 20-23 MM THICK, 2000-2500 MM



FINGER JOINT SOLID PRODUCT DETAILS: \$4\$, GRADE A/B/C, THICKNESS 21-44 MM, LENGTH



E2E GROOVING PRODUCT DETAILS: GRADE A/B, 42-48 MM THICK, 900-1250 MM LENGTH, INSECT



DOORJAMB PRODUCT DETAILS: GRADE A/B/C, INSECT REPELLENT, MC UNDER 14%

WOOD WORKING & MOULDING

