

Syrefri skiltekarton

Material composition: 100 % waste paper

Grammage scope: 1000 - 2630 g/m²

Main applications: production of office supplies (ring binders, folders,), painting templates, covers, mirror frames, board games, boxes

Basic information:

- Durable and resistant to bending
- Both sides white with grey core
- Environmentally friendly, made from 100% recyclable materials
- pH value 7

STANDARD TECHNICAL SPECIFICATION

| Parameter | Unit | Tolerance | Value | | | | | | |
|--------------------------------|------------------|-----------|-------|------|------|------|------|------|------|
| | | | 1000 | 1320 | 1590 | 1650 | 1970 | 2300 | 2630 |
| Grammage | g/m ² | +/- 5% | 1000 | 1320 | 1590 | 1650 | 1970 | 2300 | 2630 |
| Thickness | mm | +/- 5% | 1,5 | 2,0 | 2,4 | 2,5 | 3,0 | 3,5 | 4,0 |
| Humidity | % | +/- 2% | 6,5 | 6,5 | 6,5 | 6,5 | 6,5 | 6,5 | 6,5 |
| Bulk | cm ³ | Mini | 1,50 | 1,51 | 1,51 | 1,51 | 1,52 | 1,52 | 1,52 |
| Taber stiffness - longitudinal | MD | +/- 10% | 4640 | 6980 | - | - | - | - | - |
| Taber stiffness - transversal | CD | +/- 10% | 1300 | 2750 | - | - | - | - | - |

Storage conditions:

Paper should be stored in a dry place in its original packaging. Prior to use in production, air conditioning of an open paper pallet is required for a minimum of 24 hours in the conditions of the production hall.

Note: The aforementioned parameters are reference values and can be subject to change without prior notice.

TECHNICAL SHEET

