

Dobbeltklæber

MediaTac™ is a 0.5 mil (12µ) clear PET film, coated on both sides with a pressure sensitive acrylic adhesive, one of which is protected by a bleached clay coated Kraft paper siliconized on both sides with a differential release. The adhesive is self-wound on the release liner.

- DEVELOPED FOR PHOTO LABS WHERE A HIGH GRADE OF MOISTURE STABILITY WITHIN THE MOUNTING FILM IS REQUIRED
- IDEAL FOR HIGH-VOLUME MOUNTING, INCLUDING PRE-COATING BOARDS AND IMAGE DECAL APPLICATIONS
- RECOMMENDED FOR MOUNTING PRINTS TO SMOOTH, POROUS SUBSTRATES, SUCH AS WHITE DISPLAY BOARD, FOAM BOARDS, GATORFOAM™ AND TEMPERED HARDBOARD

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Adhesive	Acrylic (Pressure Sensitive)
Film	Clear PET
Adhesive	Acrylic (Pressure Sensitive)
Release Liner	2 Side Clay Coated, 2 Side Siliconized Kraft

PRODUCT CHARACTERISTIC

Film Thickness	0.5 mil (12µ)	2.5 mil (62µ)
Adhesive Layer	1 mil (25µ) on each side	
Adhesive pH	Neutral	
UV Protection Factor	Not Applicable	
Outdoor Durability	Not Applicable	
Service Temperature Range	-4°F to 248°F (-20°C to 120°C)	
Shelf Life	1 year	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

