

Filt



Technical information

Woolfelt made of Pure New Wool in 1,2,3,4 and 5 mm thick and 90 colours on rolls with a width of 183cm and a length of +/- 20m. We do not have a minimum order quantity and almost everything is always in stock.

TECHNICAL DATA

- PURE NEW WOOL conform "international wool secretariat"
- NON TOXIC conform Öko-Tex Test no. 990585
- Made in EC
- INFLAMMABLE conform UNE 23735 Class M1, NEN-EN-13501 Class A1
- SOUND ABSORPTION according to UNE-EN ISO 354:2004 up to 0,82αs (5mm) and 0,56αs (3mm)
- MARTINDALE TEST 15000 CONFORM UNE-EN-ISO 12947/14465
- PILLING RESISTANCE Degree 3 conform UNE-EN-ISO 12945-2-2001
- TEAR RESISTANCE conform UNE-EN-ISO 13936-2 in length 2,3 in width 1,8
- CHANGE in dry cleaning in length -1,0% in width 0,0%
- CHANGE in hand wash (first time) in length max. -8,0% in width max. -9,5%
- 100% RECYCLABLE

MAINTENANCE

- Vacuum
- Chemical cleaning / hand wash
- Iron lukewarm

ADDITIONAL TREATMENTS ON REQUEST

With a minimum order of 20m we can add one of the treatments listed below

- Anti-moth
- Extra dirt repellent
- Extra colour fast
- Shrink free
- Your own colour

CUSTOM MADE

We can (laser)cut or punch our Woolfelt in every shape and dimension. We can inform you about the possibilities and advise you about the application of the felt in your project.

TECHNICAL SHEET





J&M Handel ApS

is authorized to place the label "Classification of Reaction to Fire of Construction Products" according to the report N° 2018AN1573



aitex
textile research institute

**CLASSIFICATION OF REACTION TO FIRE OF:
CONSTRUCTION PRODUCTS**

N° 18AN1573

The sample reference:

"PAÑO 1º FELTINA"

has been tested according to the standards EN ISO 11925-2:2010 and EN 13823:2010+A1:2014. The classification according to standard EN 13501-1:2007+A1:2009 is:

"B-s1,d0"

Alcoy May 22nd 2018



Celia Dolça
HEAD OF FIRE BEHAVIOUR LAB.