



Liqflow

X-PROOF GRINDER PUMPS

The Next Generation of Grinder



Explosion proof grinder pump series designed to handle wastewater applications requiring high capacity, high head, and high flow

BLADE

TECHNICAL DATA

- Heads to: 73 m
- Flows to: 9.4 l/s
- Discharge size: DN50, DN65, DN80
- Motor: 2.2, 4, 5.5, 7.5, 11 kW
- RPM: 2900

APPLICATIONS

- Municipal
- Commercial
- Institutional
- Light Industrial



ADVANCED
CUTTER
TECHNOLOGY

EXPLOSION
PROOF
DESIGN

LONG
LASTING
DEPENDABILITY

LIQFLOW X-PROOF GRINDER PUMPS

1. Plug-n-play cord simplifies pump installation with its quick disconnect capability
2. Oil-Filled Motor for optimal motor cooling and maximum bearing life
3. Stainless steel hardware provides resistance against corrosion to extend pump life
4. Moisture detection probe alerts pending seal issues before water can enter the motor
5. Vortex impeller design greatly reduces clogging issues due to troublesome objects
6. Exclusive Slicer™ slices with the full torque of the motor acting on a small area to provide the ultimate solution in solids reduction
7. Available in vertical or horizontal discharge (18 Frame only) for simple installation and replacement
8. Double mechanical seals provide maximum motor protection
9. Heavy duty, oil-lubricated bearings extend pump life
10. Large lifting Bail allows for easy installation
11. Explosion proof design gives an added piece of mind for pump operation and safety; Class I Group C & D Division 1 motors as standard with Class F insulation system



Blade accessory options:

Break Away Fitting (BAF)

Vertical - used with current grinders/sewage ejectors
Horizontal - BAF-3x3

Control Panels

Family of Control Panels provides cost effective and reliable pump station operation.

Level Control Systems

Modularized control assemblies are available including mechanical floats and the ESPS™ (Environmentally Sealed Pressure Switch).