



LUBINOL LFD

SAE 15W-40

Multigrade engine oils

Product Description

LubInol LFD SAE 15W-40 engine oils are produced with mineral base stocks and selected additives. The dispersancy provides a clean engine and prevents sludge built-up. Additionally, the additives assure protection against thermal oxidation, corrosion and wear.

Product Benefits

LubInol LFD SAE 15W-40 are economical crankcase oils, and they may be used for passenger cars gasoline and diesel engines as well. They are providing performance reserves even at high loading and care for long engine life.

Specifications

API SF / CD

Nominal Values

LUBINOL LFD SAE 15W-40	Unit	Value	Method
Density at 15°C	kg/m ³	882	DIN 51 757
Kinematic viscosity at 40°C	mm ² /s	103	DIN 51 562
Kinematic viscosity at 100°C	mm ² /s	14,0	DIN 51 562
Viscosity index		139	DIN ISO 2909
Dynamic viscosity at -20°C	mPa.s	6500	DIN 51 377
Dynamic viscosity at -15°C	mPa.s	-	DIN 51 377
Pourpoint	°C	-33	DIN ISO 3016
Flash point	°C	222	DIN ISO 2592

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further information to be available by MSDS.