

LuBinol[®]
MADE IN GERMANY



PRODUCT RANGE

Index

Multigrade Engine Oils for Passenger Cars and Light Commercial Vehicles.....	2-3
Monograde Engine Oils.....	3
Multigrade Racing Oils.....	4
Four Stroke Oils for Motorcycles.....	4
Two Stroke Engine Oils.....	5
Automatic Transmission Fluids.....	5
Automotive Gear Oils.....	6
Multigrade Engine Oils for Mixed Fleets.....	6
Multigrade Engine Oils for Commercial Vehicles.....	7
Universal Oils for Agricultural and Construction Machinery.....	7
Hydraulic Oils.....	8
Slideway Oils.....	8
Heat Transfer Oils.....	8
Industrial Gear Oils.....	9
Turbine Oils.....	9
Anti Freezes.....	9
Greases.....	10
Brake Fluid.....	10

MULTIGRADE ENGINE OILS FOR PASSENGER CARS AND LIGHT COMMERCIAL VEHICLES

Product	Performance		Description
	API	ACEA	
Lubinol LVS SAE 0W-40	SN/CF	A3/B4	Fully synthetic high-performance oil for gasoline and diesel engines. Specification according VW 503.01, MB-229.3.
Lubinol LVM SAE 5W-30		C3	High performance low friction oil, which extends lifetime of exhaust-after-treatment-devices (Diesel Particulate Filter; Catalytic Converter) of gasoline- and diesel-engines. specification according MB-229.51 and VW 504.00/507.00 and BMW Longlife-04
Lubinol LBM SAE 5W-30	SM/CF	C3	Fully synthetic high performance low friction oil for gasoline- and diesel-engines in passenger cars. Specification according MB-229.51, BMW LL-04 and VW 502.00 / 505.00 / 505.01 (unit-injector)
Lubinol FOS SAE 5W-30	SN/CF	A3/B4/C3	High-performance low friction oil for passenger car engines. Meets in particular the requirements of Ford WSS-M2C 913-B and WSS-M2C 913-A.
Lubinol SMG SAE 5W-30	SN	A5/B5/C2	All-seasons oil for all those passenger car engines, which require fuel economy (FE) Oils. Meets i.a. requirements of Hyundai, KIA, GM 6094 M, Ford WSS M2C 913-C and WSS-M2C 929-A.
Lubinol LBM SAE 5W-40	SN/CF	A3/B4/C3	Fully Synthetic low friction oil of the new "Low SAP"- generation for passenger car engines with exhaust after treatment devices (catalytic converter, diesel particulate filter) and without. Meets i.a. the requirement of Porsche. Specification according VW 502 00 / 505 00 / 505 01 (Pumpe-Düse), BMW Longlife-04 and MB-229.3
Lubinol LHC SAE 5W-40	SN/CF	A3/B4	Newest generation high-performance low friction oil for passenger cars and light commercial vehicles. Meets i.a. the requirements of Porsche and BMW Longlife-98, VW 502.00 / 505.00 and MB 229.3
Lubinol LSS SAE 10W-40	SL/CF	A3/B4	Semi-synthetic low friction oil for gasoline and diesel engines. Excellent suitable in modern passenger car engines, turbo or non turbo charged. Meets i.a the requirements of VW 505 00, MB 229.1
Lubinol LMO SAE 15W-40	SL/CF	A3/B4	High-performance oil for gasoline and diesel engines in passenger cars and light commercial vehicles. Especially suited for turbo chargers and multivalve engines. Specification according VW 505.00 and MB-229.1.
Lubinol LHC SAE 5W-30	SN/CF ACEA	A3-/B4-12	Newest generation high-performance low friction oil for passenger cars and light commercial vehicles. Meets i.a the requirements of Porsche A 40, Renault RN 0700/0710, Opel GM-LL-B-025 , PSA B71 2296, VW 502 00 / 505 00, SKODS, AUDI, SEAT, MB 229.3
Lubinol DPF SAE 5W-30		A3-/B4- /C3-04	High performance low friction oil for passenger cars gasoline- and diesel-engines of the VW-Group, also for FSI. Suitable for vehicles with VW Longlife-Service. Special oil for diesel engines with Diesel Particular Filter (DPF). Meets i.a. the requirements of VW 504 00 / 507 00, MB 229.51, BMW Longlife-04
Lubinol BW SAE 5W-40	SN/CF	A3/B4	High performance low friction oil for gasoline and diesel engines. Meets i.a. the requirements of BMW Longlife-01, MB 229.5, MB 226.5, Porsche A 40, VW 502 00 / 505 00, Renault RN0700 and RN0710, PSA B71 2296, Opel GM-LL-B-025 MB 229.5.

Lubinol TSX
SAE 10W-30

SN/CF A3-/B4-08

Semi-synthetic low friction oil for gasoline and diesel engines. Excellent suitable in modern passenger car engines, turbo- or non-turbo charged. Meets i.a the requirements of VW 505 00, MB- 229.1, Toyota, Nissan, Honda, Mitsubishi, Isuzu, Subaru, Daihatsu, Mazda, Suzuki KIA, Hyundai, SaangYong, Daewoo.

Lubinol OSI
SAE 10W-40

SN/CF A3-/B4-08

Semi-synthetic low friction oil for gasoline and diesel engines. It is produced by blending high quality synthetic oils and mineral base stocks and additives of most progressive technology. Excellent suitable in modern passenger car, turbo or non-turbo charged. Meets i.a the requirements of VW 505 00 and MB 229.1

Lubinol RX
SAE 15W-40

SN/CF A3-/B4-08

High performance multigrade motor oil to be used in passenger cars gasoline and diesel engines. It is produced by blending high quality base oils and additives of most progressive technology. Suitable also under severe operating conditions in modern passenger car engines, turbo- or non-turbo charged. Meets i.a the requirements of VW 505 00 and MB 229.1

Lubinol LB
SAE 20W-50

SL/CF A3-/B4-12

Multigrade motor oil to be used in passenger cars gasoline and diesel engines. It is produced by blending high quality base oils and additives of most progressive technology. Suitable also under severe operating conditions in modern passenger car engines, turbo- or non-turbo charged. Meets i.a the requirements of MB 229.1

Lubinol LFD
SAE 10W-40

SF/CD

Multigrade engine oils for prior gasoline and diesel engines with turbo chargers and without. Qualified for all-seasons use in temperate zones (15W/40) and in warm zones (20W/50)

Lubinol LMD
SAE 15W-40

SF/CF
CF-4 A3, B4

Multigrade engine oil for gasoline and diesel engines of conventional designs with turbo chargers. Qualified for all-seasons use.

MONOGRADE ENGINE OIL

PRODUCT NAME

PERFORMANCE LEVEL

PRODUCT DESCRIPTION

API

Lubinol LL
SAE 10W
SAE 20W-20
SAE 30
SAE 40
SAE 50

SF/CF

Economical HD oils for heavily loaded diesel engines. Also suitable for gasoline engines which make normal demands on the lubricant and for those where no higher alloyed engine oils are necessary or specified.

Lubinol LD
SAE 10W
SAE 20W-20
SAE 30
SAE 40
SAE 50

SF/CF

HD oils for gasoline and diesel engines which make normal demand on the engine oil and for those where no higher alloyed engine oil is needed or specified. Depending on the manufacturer's specification Promotol FD monograde oils can also be used as aircompressor oils according DIN 51 506.

MULTIGRADE RACING OILS

PRODUCT NAME	PERFORMANCE LEVEL		PRODUCT DESCRIPTION
	API	ACEA	
Racing Oils SAE 5W50	SN/CF	A3/B3	Fully synthetic high performance low friction oil for racy high-tech gasoline and diesel engines of passenger cars.
Racing Oils SAE 10W60	SN/CF	A3/B3	Fully synthetic high performance low friction oil for racy high-tech gasoline and diesel engines of passenger cars.

FOUR STROKE ENGINE OILS

PERFORMANCE LEVEL	PERFORMANCE LEVEL		PRODUCT DESCRIPTION
	API	ACEA	
Motorcycles 4-stroke SAE 10W40	SL	A3	High performance special oil for any motorcycles with air- or water-cooled 4-stroke engines of highest output. Meets i.a. the requirements of JASO MA.
Motorcycles 4-stroke SAE 10W50	SL	A3	High performance special oil for any motorcycles with air- or water-cooled 4-stroke engines of highest output. Meets i.a. the requirements of JASO MA.
Motorcycles 4-stroke SAE 10W60	SL	A3	High performance special oil for any motorcycles with air- or water-cooled 4-stroke engines of highest output. Meets i.a. the requirements of JASO MA.
Motorcycles 4-stroke SAE 15W50	SL	A3	High performance special oil for any motorcycles with air- or water-cooled 4-stroke engines of highest output. Meets i.a. the requirements of JASO MA.
Motorcycles 4-stroke SAE 20W50	SL	A3	High performance special oil for any motorcycles with air- or water-cooled 4-stroke engines of highest output. Meets i.a. the requirements of JASO MA.

TWO STROKE ENGINE OILS

PRODUCT NAME	PERFORMANCE LEVEL	PRODUCT DESCRIPTION
--------------	-------------------	---------------------

API **ACEA**

2-stroke VS	TS (JASO FD) (ISO-L-EGD)	Fully synthetic high-performance 2-stroke oil for water- or air-cooled racing and road-engines with separate or petrol lubrication. Developed especially for high speed engines.
2-stroke SS	TS (JASO FD) (ISO-L-EGD)	Semi-synthetic 2-stroke engine oil for universal use in petrol and separate lubricated units, especially in high-performance engines of motor vehicles, mopeds, chain saw drives, snowmobiles etc.

AUTOMATIC TRANSMISSION FLUIDS

PRODUCT NAME	PERFORMANCE LEVEL	PRODUCT DESCRIPTION
--------------	-------------------	---------------------

ATF II D	GM DEXRON II D	Advanced transmission fluid for universal use in automatic transmissions, steering boosters and hydraulic units. Meets i.a. the requirements of MB 236.7, Voith, Allison C-3C-4, MAN 339 type D, ZF TE ML 33D, 04D, 09A, 11 A, 14A, Ford SQM 9010B; Ford M2C-138CJ, 169H, 165A and Caterpillar TO-2.
ATF III H	GM DEXRON III H	Gear oil to be used in automatic transmissions, steering boosters, fluid couplings, hydrodynamic converters and for hydraulics in motor cars, trucks, buses and construction vehicles, if an ATF of Dexron III H type is recommended. Meets i.a. the requirements of MB 236.1 & 236.5, Voith 55.6335.30 Allison C-4, MAN 339 Typ Z1 & V4; Mercon, ZF TE ML 02F, 03D, 04D, 05D, 11B, 14A, 17C and Caterpillar TO-2.
ATF JP	GM DEXRON III H	Automatic Transmission Fluid for Asian vehicles. To be used in automatic transmissions, steering boosters, fluid couplings, hydrodynamic converters and for hydraulics in motor cars, trucks, buses and construction vehicles. Meets i.a. the requirements of JASO M013 Type 1A, Toyota Type D-2, T-1, T-11 and T-1V, Mazda ATF D-II, ATF M-3, Mitsubishi SP-II and SP-II, Suzuki ATF Oil and ATF Oil Special, Mercon, Kia, Hyundai and Nissan Matic Fluid C, D und 1.
ATF Plus 4	GM DEXRON III	Synthetic high performance ATF for life-time use in modern motorcar transmissions. Exceeds any Dexron II requirements and it is also miscible with Dexron ID-1 and Dexron II-ATF5. Meets i.a. the requirements of Voith Turbo corresponding H5.6336.35 for extended drain intervals (200.000 km) and ZF-TE ML 11B.
ATF MB III	GM DEXRON III	Life-Time ATF for Mercedes Automatic Transmissions. It is made from synthetic base oils and such from the synthesis technology has an outstanding performance package. Meets i.a. the requirements of MB 236.11, MB 236.12 and MB 236.14.
ATF Dexron VI	GM DEXRON VI	Automatic transmission fluid suitable for many European, American and semi-CEM B6. Meets i.a. the requirements of Audi G 052 025-A2, Audi G 052 162-A1, BMW LA2034, BMW LT 71141, BMW 5 Series, ETL 80725, BMW TP4E/Dynapar ATF +3+4, Daihatsu NAG 1, Volvo 4-6 Speed, VW T62162, Honda Z-1, Isuzu WA-1, JWS-3300, JATCO SR10 PLUS, JWS 3300, Mazda ATF-II, ATF-MV, Nissan Matic DU/S, N402, NWS-9838, Subaru SP-4, SP-II, Toyota T-1, T-3V, Toyota WS, MAN 339 type V-TX-Z7, T2-Z2, MB 236.1, MB 236.2, MB 236.5, MB 236.6, MB 236.7, MB 236.9, MB 236.10, MB 236.11 and ZF TE ML 02F, 03D, 04D, 05D, 09, 11B, 14A, 16D, 16E, 17C.
ATF Spezial CVT		Hochleistungsautomatgetriebeöl, welches für die neueste Generation von CVT-Getrieben entwickelt wurde. Erfüllt u. a. die Anforderungen von MB 236.20/M 8 A 001 989 40 03, BMW 8322 0 136 376, BMW 8322 0 429 159, Ford CVT 23, Ford WSS-M2C 929-A, GM/Saturn DEK-CVT, VW G 052 160, JASO M338, Mitsubishi NS-IVSP-III-CVT J-1, Mopar CVT-F-4, Hyundai/RA SP-II, Suzuki TCM6-4/Nissan NB-II, Toyota, Subaru und Daihatsu TC.

ATF DSG

Hochleistungsautomatgetriebeöl, welches für die neueste Generation von DSG-Getrieben entwickelt wurde. Erfüllt u. a. die Anforderungen von Audi und VW Doppelkupplungsgetriebe, die das ATF-Öl für Teile-Nr. TL 521-82 benötigen. Erfüllt u. a. die Anforderungen von Audi / Volkswagen / Seat / Skoda 02D50, 02 500 und DL 501, BMW-7D09X0, DCF70 Clotrom / Nissan / Peugeot 6DCT501, Ford / Getrag 6DCT450, DCF161 und DCF1206, Mercedes-Benz 02C230 und IF 051903, Porsche ZF 7D17SHL, 7D17SHLA, 7D175FL, 7D17, 7D17H-LA, 7D1775 und 7D177A, Mitsubishi-6DCT140 und Volvo 6DCT40.

AUTOMOTIVE GEAR OILS

PRODUCT NAME	PERFORMANCE LEVEL	PRODUCT DESCRIPTION
Gear Box 4 SAE 80W SAE 80W-90 SAE 80W-90	GL-4	Multipurpose EP gear oil for synchromesh and non-synchromesh manual gears as well as for certain steering gears and axle drives. Meets i.a. the requirements of MB 235.1, MAN 341 Z-I and ZF TE-ML 02A, 16E, 17A, 19A
Gear Box 5 SAE 80W-90 SAE 85W-90 SAE 85W-140	GL-5	Hypoid gear oil for heavily stressed rear axle drives, distributor-, intermediate- and secondary gears in motor vehicles and machine tools. Meets i.a. the requirements of MAN 342 M-2, MIL-L-2105D, ZF TE-ML 05A, 07A, 12E, 16B/C/D, 17B, 19B
Gear Box VS 4.5 SAE 75W90	GL-4/5	Fully synthetic universal gear oil of the highest performance class with excellent fuel economy properties and extreme load-carrying capacity. Meets the requirements of MIL-PRF 2105.

MULTIGRADE ENGINE OILS FOR MIXED FLEETS

PRODUCT NAME	PERFORMANCE LEVEL		PRODUCT DESCRIPTION
	API	ACEA	
Lubinol LMF SAE 10W-40	CI-4 CF/SL	E7/B4/A3	Maximum performance low friction oil for modern diesel and gasoline engines with turbo charger. Meets i.a. the requirements of Cummins CES20077/20078, Renault Truck RLD/RLD-2, Mack EO-M Plus, MTU type 2 and Caterpillar ECF-1a and ECF-2. Specification according Deutz DQC III-05, MB- 228.3, Volvo VDS-3, MAN M3275,
Lubinol LMF SAE 15W-40	CI-4 CF/SL	E7/B4/A3	Maximum performance oil for diesel and gasoline engines. Meets i.a. the requirements of Renault Truck RLD/RLD-2, Mack EO-M Plus, MTU type 2 and Caterpillar ECF-1a and ECF-2. Specification according MB-228.3 /229.1, Volvo VDS-3, MAN M3275, Mack EO-N, Renault VI RLD-2 and Cummins CES 20078.
Lubinol MF SAE 10W-40	CI-4 CF/SL	E7/B4/A3	High performance low friction oil for highest demands. Meets i.a. the requirements of MAN M3275, MB 228.3 / 229.1, Volvo VDS-3 and Caterpillar ECF-1a and ECF-2. Specification according Deutz DQC III-05.
Lubinol MF SAE 15W-40	CI-4 CF/SL	E7/B4/A3	High performance low friction oil for highest demands. Meets i.a. the requirements of MAN M3275, MB 228.3 / 229.1 and Caterpillar ECF-1. Specification according Volvo VDS-3.

MULTIGRADE ENGINE OILS FOR COMMERCIAL VEHICLES

PRODUCT NAME	PERFORMANCE LEVEL		PRODUCT DESCRIPTION
	API	ACEA	
Truck plus LSAP SAE 10W-40	CI-4	E9/E7/E6	Semi-synthetic high performance low friction diesel oil. Due to reduced sulfur-, phosphor- and ash content suitable for exhaust after-treatment systems (Euro V standard). Meets i.a. the requirements of MTU type 3.1, Renault RXD/RGD, Mack EO-M Plus, Deutz DQC IV-10 LA, Volvo CNG and Scania LA. Specification according to MAN M3477, MAN 3271-1, MB-228.51, Volvo VDS-3, Mack EO-N and Renault VI RLD-2.
Truck plus MSAP SAE 15W-40	CJ-4/SM	E9/E7	Ultra high performance low emissions heavy duty engine oil, recommended for four-stroke naturally aspirated, turbocharged, and supercharged diesel engines. Meets i.a. the requirements of MB 228.31, MAN 3275 / 3575, MTU type 2.1, DDC 93K218, Caterpillar ECF-3 / ECF-2 / ECF-1a, Cummins CES20081. Specification according to Volvo VDS-4, Mack EO-O Premium Plus and Renault VI RLD-3.
Truck plus XH SAE 10W-40	CI-4/SL	E7/E4	High performance UHPD low friction oil for Euro V commercial vehicle engines. Meets i.a. the requirements of MTU type 3, Renault RXD, Deutz DQC III-05 and Scania LDF-2. Specification according to MAN M3277, MB-228.5, Volvo VDS-3, Mack EO-N and Renault VI RLD-2.
Truck plus UHPD SAE 10W-40	CI-4/SL	E7/E4	Semi-synthetic high performance low friction oil UHPD for Euro V commercial vehicle engines. Meets i.a. the requirements of MTU type 3, Renault RXD, Deutz DQC III-05, Scania LDF-2, MAN M3277, MB 228.5 / 229.1, Volvo VDS-2, Mack EO-L and Caterpillar ECF 1-a.

UNIVERSAL OILS FOR AGRICULTURAL AND CONSTRUCTION MACHINERY

PRODUCT NAME	PERFORMANCE LEVEL		PRODUCT DESCRIPTION
	API	ACEA	
Agricultural STOU SAE 10W40	CF CG-4 SF GL-4	E3	All-seasons multigrade oil to be used in all types of agricultural machinery. Meets i.a. the requirements of MB 227.1, Ford M2C 159B, Allison C-4, Case MS 1118, 1207, 1209, John Deere JDM J27, Massey Ferguson CMS M 1139/1144 /1145, ZF TE-ML-06B / -06C / -06D, Caterpillar TO-2 and MAN 271.
Agricultural STOU SAE 80W-85W	GL-4		For supplying transmissions, hydraulics and wet brakes in tractors, forestry and construction machinery of any types. Meets i.a. the requirements of Ford M2C134D, CNH MAT3525, John Deere JDM J20C and J20D, VCE WB101, ZF TE-ML-03E/-05F and Massey Ferguson CMS M1141 /1143.

HYDRAULIC OILS

PRODUCT NAME

PERFORMANCE LEVEL

PRODUCT DESCRIPTION

ISO-VG

Hydraulic Oil
HLP

10, 22, 32,
46, 68

Mineral oil-base hydraulic oil. Meets and exceeds the requirements of DIN 51 524 part 2 (HLP), ISO 6743/3 (HM) and AFNOR NF E48 602 (HM).

Hydraulic Oil
HCP

32, 46, 68

High-performance EP hydraulic oil with very good viscosity temperature characteristics. Meets and exceeds the requirements of DIN 51 524 part 3 (HVL), ISO 6743/4 (HV) and AFNOR NF E 48 602 (HV).

SLIDEWAYS OILS

PRODUCT NAME

PERFORMANCE LEVEL

PRODUCT DESCRIPTION

ISO-VG

Slide way Oil

68, 220

For lubricating the slide ways on machine tools, of gear units and all kinds of advance devices. For hydraulic systems of all kinds of pumps and engines. Recommended for use in central lubricating systems. Meets the requirements of DIN 51 524 part 2 (HLP) and DIN 51 517 part 3 (CLP), classification of DIN 51 502 in the type of materials lubricant oil CGLP.

HEAT TRANSFER OILS

PRODUCT NAME

PERFORMANCE LEVEL

PRODUCT DESCRIPTION

Heat Transfer Oil

22, 32, 46

Heat transfer oil of low vapor pressure, high heat capacity and excellent thermic and oxidative stability. For indirect heating in industry and shipping. Meets the requirements placed on heat transfer medium of DIN 51 522.

INDUSTRIAL GEAR OILS

PRODUCT NAME	PERFORMANCE LEVEL	PRODUCT DESCRIPTION
--------------	-------------------	---------------------

Heat Transfer Oil	100, 150, 220, 320,460	EP gear and circulating oil for use in heavily loaded industrial gears and for use at high sliding speeds and roller pressings. Meets and exceeds the requirements of DIN 51 517 part 3 (CLP).
-------------------	------------------------	--

TURBINE OILS

PRODUCT NAME	PERFORMANCE LEVEL	PRODUCT DESCRIPTION
--------------	-------------------	---------------------

Turbine-Oil	32,46, 68	For lubricating and cooling the bearings as well as pressure transfer medium for power control systems in steam and water turbines and turbo compressors. Meets the requirements of DIN 51 515 part 1 (LTD), ISO DP 6743/5 and JIS K2213 type 2.
-------------	-----------	--

ANTI FREEZES

PRODUCT NAME	PRODUCT DESCRIPTION
--------------	---------------------

Antifreeze GW-11 Concentrate	Prediluted antifreeze for water-cooled combustion engines. Also suitable for aluminium engines. Protects the radiator against rust, corrosion and calcification and ensures frost protection down to -40°C. Meets the specification of BMW, Fiat, Ford, General Motors, Mercedes-Benz, and Peugeot.
---	---

Antifreeze GW-11-40°C	Concentrated antifreeze for water-cooled combustion engines. Also suitable for aluminium engines. Protects the radiator against rust, corrosion and calcification and, depending on the concentration used, ensures frost protection down to -40°C. Corresponds to the specifications of BMW, Fiat, Ford, General Motors, Mercedes-Benz, Peugeot.
----------------------------------	---

Antifreeze GW-12 Concentrate	Silicate-free concentrated antifreeze for water-cooled combustion engines. Also suitable for aluminium engines. Protects the radiator against rust, corrosion and calcification and depend on the concentration used, ensures frost protection down to -40°C. Compatible with all branded products (also VW G11). Qualifications VW TL 774-D/F (G12+), MB 325.3, Ford WSS-M 97B44-D, Audi, SEAT, SKODA TL 774-D/F, MAN 324, MTU MTL 5048.
---	---

Antifreeze GW-12 -40°C	Prediluted silicate-free antifreeze for water-cooled combustion engines. Also suitable for aluminium engines. Protects the radiator against rust, corrosion and calcification and ensures frost protection down to -40°C. Compatible with all branded products (also VW G11). Qualifications: VW TL 774-D/F (G12+), MB 325.3, Ford WSS-M97B44-D, Audi, SEAT, SKODA TL 774-D/F, MAN 324 SNF, MTU MTL 5048.
-----------------------------------	---

GREASES

PRODUCT NAME	Identification according To DIN 51 502	PRODUCT DESCRIPTION
Mehrzweckfett K2K-30 (Multipurpose grease)	K2K-30	Lubricating grease DIN 51825 – K2K-30, consistency class NLGI 2. Lithium grease for normally loaded rolling and plain bearings. Operating temperature range: -30 to +130°C.
EP-Langzeitfett KP2K-30 (Long-life grease)	KP2K-30	Lubricating grease DIN 51825 – KP2K-30, consistency class NLGI 2. Lithium grease for highly loaded rolling and plain bearings as well as for sliding surfaces with highly compression stress. Operating temperature range: -30 to +130°C.
Mehrzweckfett (Grafit) KF2K-30 (Multipurpose grease)	KF2K-30	Lubricating grease DIN 51825 – KF2K-30, consistency class NLGI 2. Graphite containing lithium grease for normally loaded rolling and plain bearings as well as for sliding surfaces with high compression stress. Operating temperature range: -30 to +130°C.
Mehrzweckfett (Grafit) KPF2K-30 (Multipurpose grease)	KPF2K-30	Lubricating grease DIN 51825 – KPF2K-30, consistency class NLGI 2. Graphite containing lithium grease (MoS ₂) for highly loaded rolling and plain bearings with normal high speed, as well as for sliding surfaces with high compression stress. Operating temperature range: -30 to +130°C.
Spezial-Fleissfett ZSA MP00G-40 (Fluid grease)	MP00G-40	Lubricating grease DIN 51502 – MP00G-40, consistency class NLGI 00. Lithium fluid grease on basis of mineral oils for closed gears which require grease lubricants. Operating temperature range: -40 to +100°C.
Spezial-Fleissfett ZSA KHCP00G-40 (Fluid grease)	KHCP00G-40	Lubricating grease DIN 51502 and DIN 51 825 – KHCP00G-40, consistency class NLGI 00. Lithium fluid grease on the basis of synthetic base oils for closed gears which require grease lubricants. Operating temperature range: -40 to +100°C.
LKW EP-Radlagerfett KP2N-30 (Wheel bearing grease)	KP2N-30	Lubricating grease DIN 51502 – KP2N-30, consistency class NLGI 2. Lithium complex grease for highly loaded rolling and plain bearings at high temperature, short-term up to 220°C. Operating temperature range: -30 to +140°C.

BRAKE FLUID

PRODUCT NAME	PRODUCT DESCRIPTION
Brake fluid Dot 4	Heat transfer oil of low vapor pressure, high heat capacity and excellent thermic and oxidative stability. For indirect heating in industry and shipping. Meets the requirements placed on heat transfer medium of DIN 51 522.



Lubinol UG

Strehleener Street 12-14,
01069 Dresden, Germany

Tel. +49 - (0) 351 160 56 831

Fax. +49 - (0) 351 426 66 578

E-Mail: info@lubinol.com

Web: www.lubinol.com