

Maven digital repeater EMEA-APAC Exo high power repeater

Datasheet version 2.2

**Outstanding
Performance**

**End to end
Digital platform**

**Always
Future-proof**

**Overall
Cost efficiency**

**More
Sustainable**

Maven Wireless offers new solutions for wireless coverage in all parts of the world. Our products are end to end digital and future-proof, comes with the best performance and cost efficiency you can find. We also have high marks on sustainability and a burning passion for making our customers and end-users life safer, better and easier by securing 100% wireless coverage.

Exo digital repeater



Exo specification

General

Mains power	85 – 264 VAC, -72 – -36 VDC optional
Power consumption	280 W max fully loaded
Management	Ethernet 10/100/1000, micro USB, USB accessory connector
Remote Access	Optional 4G modem
Operating temperature	-25 to +55 °C
Ingress protection	IP66
RF interface	Up to 2 bands in one enclosure
Antenna port	4.3-10 or 7/16 optional
System Gain	60 to 90 dB in 0.1 dB steps
Gain flatness	1 dB pp
Noise figure	< 3 dB at max gain

RF Parameters

DL Output power	+43 dBm per band																				
UL Output power	+30 dBm per band																				
RF input range	+17 dBm, non destructive																				
Frequencies*	<table><thead><tr><th>Uplink</th><th>Downlink</th></tr></thead><tbody><tr><td>703 – 733 MHz</td><td>758 – 788 MHz</td></tr><tr><td>832 – 862 MHz</td><td>791 – 821 MHz</td></tr><tr><td>880 – 915 MHz</td><td>925 – 960 MHz</td></tr><tr><td>1710 – 1785 MHz</td><td>1805 – 1880 MHz</td></tr><tr><td>1920 – 1980 MHz</td><td>2110 – 2170 MHz</td></tr><tr><td>2500 – 2570 MHz</td><td>2620 – 2690</td></tr><tr><td></td><td>2300 – 2400 MHz</td></tr><tr><td></td><td>2500 – 2700 MHz</td></tr><tr><td></td><td>3400 – 3800 MHz</td></tr></tbody></table>	Uplink	Downlink	703 – 733 MHz	758 – 788 MHz	832 – 862 MHz	791 – 821 MHz	880 – 915 MHz	925 – 960 MHz	1710 – 1785 MHz	1805 – 1880 MHz	1920 – 1980 MHz	2110 – 2170 MHz	2500 – 2570 MHz	2620 – 2690		2300 – 2400 MHz		2500 – 2700 MHz		3400 – 3800 MHz
Uplink	Downlink																				
703 – 733 MHz	758 – 788 MHz																				
832 – 862 MHz	791 – 821 MHz																				
880 – 915 MHz	925 – 960 MHz																				
1710 – 1785 MHz	1805 – 1880 MHz																				
1920 – 1980 MHz	2110 – 2170 MHz																				
2500 – 2570 MHz	2620 – 2690																				
	2300 – 2400 MHz																				
	2500 – 2700 MHz																				
	3400 – 3800 MHz																				

Mechanical

Dimensions (height, width, depth)	670 x 383 x 270 mm
Weight	max 25 kg

Standard & Approvals

EMC & safety	Low voltage directive 73/23/EEC
EMC directive 2004/108/EC	RE&TTE directive 1999/5/EC

*) Various frequency combinations in the same enclosure are available. Contact Maven Wireless for more information.
Note: All parameters are subject to change.