

MAI<sup>®</sup> **2PUMPTAURUS**



MAN ASSISTING INNOVATIONS

... IT DOESN'T GET ANY BETTER

## MAI<sup>®</sup> 2PUMPTAURUS

### FULL SPEED AHEAD

- The greatest possible flexibility when changing location from the 1st to the 6th floor, from the 6th to the 12 floor, etc.
  - Generous conveying distances

### SAVE TIME AND MONEY

The variable conveying capacity will increase efficiency at construction sites, because time-consuming retooling has been made unnecessary. No more rights of recourse from the builder because of corrosion or paint residue on the facade. We guarantee it!

### THE ADVANTAGES AT A GLANCE

- Robust construction for the toughest uses
  - Reliable and low-cost operation
- Modular construction guarantees suitability for all performance ranges

### IT CAN ALSO OFFER

- Small but powerfull
- Extreme ease of operation
- Stainless steel guarantees freedom from corrosion

### TECHNISCHE DATEN

Operating voltage:	400V/3/PE/50Hz
Nominal power:	8,2 kW
Fusing:	32 A
Feed capacity:	5 - 100 l/min
L x W x H:	130 x 80 x 76 cm
Filling height:	76 cm
Total weight:	170 kg



MAI<sup>®</sup> International GmbH, Werkstraße 17, 9710 Feistritz/Drau  
P.O.Box 8, Austria, Europe, E-mail: mai@mai.at, Internet: www.mai.at  
Tel. +43 (0) 4245/6233-0, Fax +43 (0) 4245/6233-10

© Copyright: MAI<sup>®</sup> and MAI-PUMP<sup>®</sup> are registered trademarks of MAI<sup>®</sup> International GmbH.  
MAI<sup>®</sup> International GmbH reserves the right to alter its machine specifications and descriptions  
at any time without prior notice. EN09/2009

**MAI**  
INTERNATIONAL<sup>®</sup>