

Panasonic EBL512 G3

PACOM Unison effectively links Panasonic EBL512 G3 products with other sub-systems such as access control, alarm and video to provide a powerful, automated fire control and building management solution.

FEATURES	
REAL-TIME MONITORING	
Communication errors	✓
Hardware errors	✓
System faults	✓
Sensor values	✓
System status (e.g. power, battery)	✓
ALARMS	
Receive fire alarms	✓
Receive trouble alarms (e.g. loss of communication)	✓
Receive supervisory alarms	✓
Receive AC fail	✓
Receive battery low/battery failure	✓
ALARM HANDLING	
Acknowledge alarms	✓
Silence alarms	✓
Reset/Cancel alarms	✓
AUDIT TRACKING	
Alarm responses logged	✓
Configuration changes logged	✓
ENABLE/DISABLE EXTERNAL UNITS	
Enable/Disable detectors	✓
Enable/Disable sounders	✓
Enable/Disable ventilation outputs	✓
Enable/Disable sprinkler outputs	✓
Enable/Disable extinguisher outputs	✓
OTHER	
Isolate inputs	✓
Activate outputs	✓
Activate/Disable test mode	✓
Sound audible alerts on the operator's monitor when an alarm goes off	✓
Trigger action on cameras, doors, etc.	✓
Automatically upload panel/system data	✓
Display alarms on graphical maps	✓
Import fire panel configuration	✓

COMPATIBILITY	
PRODUCT	VERSION
PACOM Unison	5.7 or later
Panasonic EBLnet	Protocol: EBLnet United 2.7, EBL Central firmware version 2.7.1 Protocol: EBLnet G3 1.1.x, EBL Central firmware version 1.1.6 Protocol: EBLnet G3 2.2.x, EBL Central firmware version 2.2.0 Protocol: EBLnet G3 2.3.x, EBL Central firmware version 2.3.x (for Unison 5.8.0 or later)