

Schrack Seconet

PACOM Unison effectively links Schrack Seconet products with other sub-systems such as access control, alarm and video to provide a powerful, automated fire control and building management solution.

FEATURES	
REAL-TIME MONITORING	
Communication errors	✓
Hardware errors	✓
System faults	✓
Sensor values	x
System status (e.g. power, battery)	✓
ALARMS	
Receive fire alarms	✓
Receive trouble alarms (e.g. loss of communication)	✓
Receive supervisory alarms	✓
Receive AC fail	x
Receive battery low/battery failure	✓
ALARM HANDLING	
Acknowledge alarms	x
Silence alarms	x
Reset/Cancel alarms	✓
AUDIT TRACKING	
Alarm responses logged	✓
Configuration changes logged	✓
ENABLE/DISABLE EXTERNAL UNITS	
Enable/Disable detectors	✓
Enable/Disable sounders	✓
Enable/Disable ventilation outputs	✓
Enable/Disable sprinkler outputs	✓
Enable/Disable extinguisher outputs	✓
OTHER	
Isolate inputs	✓
Activate outputs	✓
Activate/Disable test mode	✓
Sound audible alerts on the Operator's monitor when an alarm goes off	✓
Trigger action on cameras, doors, etc.	✓
Automatically upload panel/system data	✓
Display alarms on graphical maps	✓
Import fire panel configuration	✓

COMPATIBILITY

PRODUCT	VERSION
PACOM Unison	5.7 or later
Schrack Seconet	ISP-IP protokoll v3.1.1 , N3-IP protocol v1.0, CAMP protocol v1.0 Schrack Seconet fire alarm centers B5-SCU-C, B5-SCU and B6-X2-C