





DIRECT-ELECTRICITY 230 V CONVECTOR WITH A FAN












- high output
- · very short response time
- suitable for interior applications with no hot water supply
- suitable for wooden interiors and wooden constructions


DIMENSIONS

width - with standard frame	303 mm
width - with covering frame	329 mm
height	125 mm
length	500 - 2500 mm

CROSS SECTION



LONGITUDINAL SECTION



FRAMES

• Standard frame (AL-aluminium)



Covering frame (AL-aluminium)




GRILLES - materials


dark bronze light bronze silver stainless steel




(shades of the grilles are only illustrative)

GRILLES - profile





st.steel-rolling-sparse¹⁾



1) the grille must be ordered with the convector due to the modification of the convector construction

Standard grilles are transverse, if you are interested in **LONGITUDI**-NAL GRILLES, please contact your sales representative.



HEATING OUTPUT

length L [mm]	heating output [W]
500	750
1000	1500
1500	2250
2000	3000
2500	3750

ACOUSTIC PRESSURE

length L [mm]	Equivalent acoustic pressure level LAeq,2m [dB]
500	25,3
1000	26,4
1500	27,5
2000	29,5
2500	30,6

measurement at a distance of 2m from the noise source at 1m height

EXAMPLE OF ORDER CODE



*orientation and length complete according to the specification of the convector

Orientation: L = left connection / P = right connection

Convectors are designed to the CONCRETE FLOOR, in case of HOLLOW FLOOR installation, please consult with your sales representative.

The standard delivery includes convector, anchoring accessories and covering grille. All other accessories (connection accessories, control elements, etc.) must be ordered and specified separately.

The technical parameters are set according to the relevant standards. In fact, they may vary depending on the location of the convector, the cover grille, the connection type.

As a part of the product development, MINIB, a.s. reserves the right of construction and price adjustments.

For more information, please contact your sales representative.



