

Related Products and Services

- ▶ **Omni-ID Exo 800** - Extremely durable hard case tag for outdoor and industrial environments
- ▶ **Omni-ID Flex 600**- Low profile, cost effective tag, ideal for office equipment and portal setups.
- ▶ **Omni-ID Flex 1200** - Low cost alternative to hard tags for applications requiring read ranges of up to 12 meters.
- ▶ **Service Bureau** - Omni-ID offers a full service bureau for printing and pre-encoding Omni-ID tags at point of manufacture.



Environmental Specifications

Storage Temperature -40 ° to +85 °C

Operation Temperature -40 ° to +85 °C

Survivability -40 ° to +85 °C

IP Rating IP65

Shock and Vibration MIL STD 810-G

Attachment Mechanical (standard)
Premium foam (option)

Certifications





RoHS approved
CE approved
ATEX/IECEX certified (option)
US&Canada (C1D1/D2) certified (option)

Warranty 1 year

1. Excludes adhesive options, consult adhesive data sheets for recommended temperature ratings.

Ordering Information

Order code 150 - GS

Order options :303 (Customization)
:304 (ATEX/IECEX certified)
:307 (US&Canada (C1D1/D2) certified)
:701 (Standard Service Bureau)

Omni-ID office locations: **US | UK | China | India | Germany**
For product or technology inquiries email: sales@omni-id.com