

## Omni-ID® Power 60/65

The Power 60 and Power 65 are active tags designed for tracking personnel and their interactions with tagged assets. Made to be clipped to clothing or worn around the neck on a lanyard, the Power 60 and 65 are ideal for applications requiring real-time information about workers.



### Applications

The Omni-ID Power 60 and 65 are ideal tags for applications requiring long range personnel tracking in varied environments such as:

- ▶ Oil and Gas platforms
- ▶ Construction sites
- ▶ Manufacturing facilities
- ▶ Personnel management

### Physical Specifications

Construction	Glass-filled Polycarbonate
Size (mm)	95.47 × 63.87 × 10.0
Size (in)	3.76 × 2.51 × 0.39
Weight (g)	53
Attachment	Lanyard/clip slots for horizontal or vertical mounting

### Dimensions



Dimensions in mm

### RF Specifications

Battery	Lithium metal pouch
Battery Life	Up to 5 years
Beacon Rate	3 - 60 sec (configurable)
Read Range	100m typical
Data Communication	433 MHz Active Radio
Protocol	Power 60 - Omni-ID Proprietary Power 65 - IEEE 802.15.4f
Configuration	EPC Gen 2 interface with data bridge functions
User Interface	Integrated button allows for asynchronous signaling
Badge Holder	Holds ISO/IEC 7810 ID-1 card

### Environmental Specifications

Storage Temperature	-20°C to +60°C
Operating Temperature	-20°C to +45°C
IP Rating	IP65
Ruggedness	4' drop to concrete Shock: 20 G's/9ms Vibration: Sinusoidal 3G 50-500 Hz Random 4G 50-500 Hz
Warranty	1 year

## Powerful Features

- ▶ Low power consumption for long battery life
- ▶ EPC Gen 2 interface for easy configuration and management
- ▶ Seamless integration with existing ProVIEW or Power 400/415 installations and infrastructure
- ▶ Designed to hold industry-standard Identification badges



### Related System Components

OMNI-V3	Omni-ID View 3 Visual display tag
OMNI-V4	Omni-ID View 4 Visual display tag
OMNI-P400/415	Power 400/415 Rugged active tag
OMNI-P100/115	Power 100/115 Industrial active tag
OMNI-NGW-2	Link Network Gateway (USB, Ethernet and 2 Radio Modules)
OMNI-MGW	Link Mobile Gateway (USB/Bluetooth)
OMNI-IANT	Industrial Antenna - omni-directional, horizontally polarized

### Ordering Information

OMNI-P60	Personnel tracking active tag, Omni-ID proprietary protocol
OMNI-P65	Personnel tracking active tag, IEEE 802.15.4f protocol
OMNI-P60-X OMNI-P65-X	Intrinsically safe versions of the above two products

### Certifications:

Europe (CE): EN 300 220-2 V2.4.1, EN 301 489-3 V1.6.  
 FCC: CFR47 Part 15.231 , CFR47 Part 15.109(a)  
 ISED: RSS-210, Issue 8 , ICES-003

Omni-ID office locations: US | UK | China | India | Germany  
 For product or technology inquiries email: [sales@omni-id.com](mailto:sales@omni-id.com)