



SMART330HMC (333mm wide) SMART450HMC (450mm wide) SMART520HMC (520mm wide)

Available options

Many, but not all, options can be combined into one configuration
Please contact Rhyguan or an authorized channel partner for more information

Unwinder upgrade	Upgrade unwind to max. roll diameter of 900mm , with more space and larger servo engine
	Upgrade to unwind rolls in both directions
Web guide upgrade	Upgrade the web-guide from edge-guide with splice table to a line-guide with splice table
Waste rewinder	The defects rewind is located slightly left of the inspection table, after the web has passed through the inspection system.
Missing label detection	Detection system to spot missing labels per lane to be inspected. 1 sensor for each lane to be inspected
Label counter	Ultra-sonic label counter
Inkjet for sequential* numbering	Provision A: allows customer to install an inkjet numbering system of choice for back-side numbering (on the liner) AFTER inspection. This includes web path preparation, and signal integration.
Inkjet for sequential* numbering	Provision B: allows customer to install a inkjet numbering system for front-side numbering PRIOR to inspection. This includes lengthening of the frame, web-path preparation, and signal integration.
Static Electricity	Passive static elimination device, for eliminating static electricity towards a ground wire. Flexible location positioning by operator when guiding static electricity through the frame towards a ground-wire. Direct connection to ground wire also possible.
	Hefeng active static elimination device for eliminating static electricity using an active current.
Automation	Full automatic batch separation and sorting system, to separate different batches and facilitate packaging
	Automatic system to remove inspected faulty labels after sheeting, by removing them automatically from the conveyor belt
	JDF/JMF connectivity Module. Use JDF data from your CRM system to automatically set cutting lengths, counting and collection. Collect management information real time from the SMART using JMF into your CRM system

* NOTE: Limitations in combining these options apply. Pls contact Rhyguan to learn more.
Information in this document is provided as-is. All specifications and availability of options are subject to change without notification Rhyguan does not warrant the accuracy or completeness of the information. Specification of an actual product may differ. Product appearance maybe different than the images shown in this document.