



TriTech.

T8 Hi Cart



TriTech Airless

TriTech.

T8

3.40
ltrs/min

0.029"

0.019"

Max tip

Use to spray

Emulsion, interior and exterior
Water or solvent based top coats
Wood preservatives
Most other medium-viscosity water or solvent based coatings

✓ Decorative ✓ Industrial ✓ Intumescent ✓ Flat out 24/7



Product Codes

110 volt 601-853 240 volt 601-844

Complete with

TriTech T380 Contractor spray gun
TriTech Contractor 517 airless tip
TriTech Contractor safety guard
1/4" x 15m textile hose assembly
QLube x 237ml piston lubricant

Specification

Flow 3.97 ltr/min
Max tip 0.031"
MWP 227 bar | 3300 psi
Motor 1565 watt PMDC
Weight 44.0 kg
Power supply 110 / 240 volt

Features

Designed, engineered and built - all in the USA
Aerospace grade materials used throughout
High grade aluminium for the control box, motor cover and heat sink - aluminium dissipates heat, as opposed to plastic which retains it
Steel cut and precision ground gears - running in synthetic grease for positive heat transfer
Frame from chrome plated heavy walled steel tubing, immensely strong and tough
TriTech proprietary carbide blend is used for the ball and seat to give a superior and positive shut off
All covered by the unique TriTech warranty