Material Safety Data Sheet May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.	U.S. Department of Labor Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1269-0443				
IDENTITY (As Used on Label and List) SINO-CRACK	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.				
Section I					
Manufacturer's Name guizhou sino quarry & mine industries corp.,Itd.	Emergency Telephone Number & Telephone Number for Information 008613098507177 CHINA				
Address (Number, Street, City, State, and ZIP Code	=				
	Date Prepared				
7FL,RUIJIN BUSINESS BLDG,GUIYANG CITY,GUIZHOU PROVINCE, P.R.CHINA	AUG 04, 2007				
Section II - Hazardous Ingredients/Identity	Section II - Hazardous Ingredients/Identity Information				
Hazardous Components (Specific Chemical Identity; Common Names(s)) PEL	A ACGIH Other Limits % TLV Recommended (optional)				
A. HAZARDOUS COMPONENTS : NONE					
B. NON-HAZARDOUS CHEMICAL COMPOU	NDS (% by weight)				
1. Inorganic Compounds					
1) Silicon Dioxide (SiO ₂)	1.5 - 8 %				
2) Aluminium Oxide (Al ₂ O ₃)	0.4 - 5 %				
3) Ferric Oxide (Fe ₂ O ₃)	0.2 - 2 %				
4) Calcium Oxide (CaO)	81 - 95 %				
5) Magnesium Oxide (MgO)	0 - 1.1 %				
6) Sulfur Trioxide (SO ₃)	0.6 - 4 %				
2. Organic Compound none					

Section III - Physical/Chemical Characteristics						
Boiling Point		Not Applicable	Specific Gravity (H ₂ O = 1)		3.22	
Vapor Pressure	(mm Hg.)	Not Applicable	Melting Point		1180°C	
Vapor Density ((AIR = 1)	Not Applicable	',' ',' ','		Not Applicable	
Solubility in Water						
Slight						
Appearance an	d Odor					
Gray Powder, N	lo odor					
Section IV - Fire	e and Expl	osion Hazard Dat	a			
Flash Point (Me	thod Used)	Flammable Limits			
Not Applicable			Not Applicable	LEL	UEL	
Extinguishing N	/ledia					
Not Applicable						
Special Fire Fig	hting Prod	cedures				
Not Applicable						
					_	
Unusual Fire ar		•	is used incorrectly s			
Explosion Hazards of proper temperature range etc., blow-out shots will occur.						
Section V - Rea	ctivity Dat	ta				
Stability	Unstable Conditions to Avoid					
	Stable X					
Incompatibility (Materials to Avoid)						
Water (Only storage)						
Hazardous Decomposition or Byproducts						
None						
Hazardous	Мау	Conditions to A	void			
Polymerization		X				
	WIII NOL	^				

Section VI - Health Hazard Data EYE CO	ONTACT : Avoid
Route(s) of Entry: Inhalation Skin Inges	stion
Avoid Avoid Avoid	t

Health Hazards (Acute and Chronic)

- 1) Skin and eye contact: Irritation, Burn
- 2) Inhalation and Ingestion : The same symptoms as getting cement or quicklime will appear.

Carcinogenicity:NTP IARC OSHA

Not Monographs Not Regulated Not

Applicable Applicable Applicable

Signs and Symptoms of Exposure

Since the product is an alkali material, skin etc. will be irritated.

Medical Conditions Generally

Aggravated by Exposure

Skin and eyes will be irritated and will burn unless immediately rinsed off.

Emergency and First Aid Procedures

If the skin comes in contact with the product, rinse it off with clean water immediately.

If eyes come in contact with it, rinse it off with clean water immediately, and consult with a doctor as soon as possible.

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled

- 1) Gather the released or spilled product with a broom or a shovel.
- 2) Mix it with a large amount of water.
- 3) Sprinkle it onto open ground.

Waste Disposal Method

- 1) Mix it with a large amount of water.
- 2) Sprinkle it onto open ground.

Precautions to Be Taken in Handling and Storing

Store it under dry condition, and wear safety goggles for eye protection, and use rubber gloves.

Other Precautions

When mixing the product with water, do not get close to holes filled with the mixture of

the product and water to avoid any accident to be caused by blown-out shots.

Section VIII - Control Measures

Respiratory Protection(Specify Type)

It is recommended to wear ordinary dust-proof mask.

Ventilation	Local Exhaust	Special
	Not Applicable	Not Applicable
	Mechanical (General)	Other
	Not Applicable	Not Applicable

Protective Gloves Ordinary Rubber
Gloves Eye Protection Safety Goggles

Other Protective Clothing or Equipment

Not Applicable

Work/Hygienic Practices

Not Applicable

Transport Requirements

The goods no special transport requirements, sea land can be