



Semi-automatic pipe bending machine

TUBOBEND 20

TUBOBEND 20

- electronic control with eightfold bending angle pre-selection and automatic sequencing
- hydraulic pipe clamping
- plane-of-bend device with three-jaw chuck and length stop device (3 length stops + 3 rotating stops incl.)
- maximum bending space by means of an exposed and swivel bending head

**B
A
S
I
C**

**C
O
M
F
O
R
T**

- SIMATIC touch panel control with user guidance and storage facility for 100 bending programs on mobile control board
- mechanical collet chuck
- adjustable bending speed
- 2-axes measuring system for the length and rotational position with digital displaying on the touch panel

Further options

- adapter for bending mandrels
- manual or automatic mandrel lubrication
- foot switch for bending and clamping function

Models

- pipe length (over mandrel): 1500 mm / 3000 mm



Fast and easy bending of pipe shapes up to \varnothing 20 mm.



Application example: heating rod made of stainless steel \varnothing 10.0 x 1.0 mm

Technical data

bending capacity (mild steel)	\varnothing 16.0 x 2.0 mm
max. bending radius ¹⁾	45 mm
bending speed (max.)	90 °/s
positioning accuracy (bending axis)	\pm 0.2 °
dimensions, approx. (LxWxH) ²⁾	1900 x 720 x 1170 mm
weight, approx. ²⁾	150 kg
connected load	0.75 kW

¹⁾ depends on the pipe diameter

²⁾ at min. pipe length

Photos, text and illustrations are subject to change.
© TRACTO-TECHNIK GmbH & Co.KG. 2012-09.