WHEELERS MOTOR OIL- WXV

SAE 5W-40

Fully Synthetic High Performance Motor Oil for Passenger Cars with Exhaust After treatment and without.

Description

Wheelers WXV SAE 5W-40 is a high-performance fuel economy oil made from synthetic base oils. It has been developed for the use in passenger cars gasoline- and diesel-engines of modern technology, also for diesel engines with pump / nozzle injection system (PD), thus also an ideal solution for light commercial vehicles.
Due to its progressive conception, it provides an extremely wide range of performances:

Wheelers WXV SAE 5W-40 provides:

- Low sulphur-, phosphorus- and ash-content reduce poisoning of catalysators in gasoline engines and decrease the built-up of particles in the diesel particulate filter (DPF) and assist thus the environmental protection by lower pollution.
- Novel high performance additivities assures optimal wear protection and best motor cleanliness.
- Excellent thermal oxidation stability reduces oil aging and allows longer drain
- intervals at maximum motor protection.
  Best low temperature properties enable unproblematic cold-start of the motor and contribute deceivingly to a longer operating life of the engine by rapid oil circulation.

Specification / Recommendation

ACEA C3 / C2
API SP
MB 229.52 / 229.51 / 229.31
VW 505 01 / 502 00 / 505 00
BMW LongLife-04
GM dexos 2

Nominal Values

Wheelers WXV SAE 5W-40	Unit	Value	Method
Density at 15°C	kg/m³	850	DIN 51 757
Viscosity at 40°C	mm²/s	80,6	DIN 51 562
Viscosity at 100°C	mm²/s	13,50	DIN 51 562
Viscosity Index		170	DIN ISO 2909
CCS at -30°C	mPa.s	6000	DIN 51 377
Pourpoint	°C	-39	DIN ISO 3016
Flashpoint	°C	234	DIN IS0 2592

Specification variations in these characteristics may occur the instructions of manufacturer must be regarded. Further informations to be available by MSDS.

Wheelers GmbH
Jubiläumsstraße 2
01139 Dresden / Germany
Tel. 49 - (0) 351 16056831