

Randers Kemiske Industri

Safety data sheet

Prepared 10-06-2013
Revision: (date) 03-10-2024
SDS version 1.9

ITEM 1: Identification of the substance/mixture and of the company/company

1.1. Product identifier

Trade name: Liquid drain cleaner
Product no.: 839.001
CAS no.: 1310-73-2
UFI: 81KA-WV10-X20C-XK8D

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended uses:

For clogged drains.

Uses advised against:

May only be used as described above, other uses must be made in consultation with the supplier.

1.3. Details of the supplier of the safety data sheet *Company name and address:*

Randers Chemical Industry A/S
Kristrupvej 158
DK-8960 Randers SØ
Tel.: 86 41 10 22
Fax. 86 41 11 45
www.kimiljo.dk

Contact person and email:

post@kimiljo.dk

The safety data sheet has been prepared and validated by:

Mediator ApS, Centervej 2, 6000 Kolding. Consultant: DH

1.4. Emergency

telephone line: +45 82 12 12 12

ITEM 2: Hazard identification

2.1. Classification of the substance or mixture CLP

(1272/2008):

Skin Corr. 1A; H314

Eye Dam.1:H318

Wording of H-phrases - see below in point 16.

2.2. Marking elements



Signal word:

Danger

Causes severe skin corrosion and eye damage. (H314)

Wear protective gloves/eye protection. (P280)

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. (P301 + P330 + P331)

IN CONTACT WITH SKIN (or hair): Take off/remove soiled clothing immediately. Rinse the skin with water. Call a POISON CENTER/doctor immediately. (P303 + P361 + P353 + P310)

IF INHALED: Move the person to a place with fresh air and ensure that breathing is facilitated. (P304 + P340)

IF IN EYES: Rinse carefully with water for several minutes. Remove any contact lenses if this can be done easily. Continue rinsing.

(P305 + P351 + P338)



Safety data sheet

2.3. Other dangers

-

Other marking:

-

Other

The product does not meet the criteria for PBT or vPvB.

SECTION 3: Composition of/information on ingredients

3.1 /3.2. Substances / Mixtures

Ingredient	Index no. / REACH Reg. no.	CAS no.	EC no.	CLP classification	wt/wt %	Note
Sodium hydroxide	011-002-00-6 / 01- 2119457892-27- xxxx	1310-73-2	215-185-5	Met. corr. 1;H290, Skin Corr. 1A;H314, Eye Dam.1;H318 Eye Irritation. 2; H319: 0.5% \dot{y} C < 2% Skin Corr. 1A; H314: C \dot{y} 5% Skin Corr. 1B; H314: 2% \dot{y} C < 5% Skin Irritation. 2; H315: 0.5% \dot{y} C < 2%	> 30	-

Wording of H-phrases - see below in point 16.

SECTION 4: First aid measures

4.1. Description of first aid measures *Inhalation:*

Seek fresh air.

Keep the casualty under supervision.

Seek medical attention in case of discomfort.

Intake:

Rinse your mouth thoroughly and drink 1-2 glasses of water in small sips.

Do not induce vomiting.

Seek medical attention immediately.

Skin contact:

Remove contaminated clothing immediately.

Wash the skin long and thoroughly with water.

Seek medical attention immediately.

Eye contact:

Wash the eye well, remove any contact lenses and rinse immediately with water (preferably from an eyewash) and seek medical attention immediately. Continue rinsing until the doctor takes over the treatment.

Other information:

When consulting a doctor, bring the safety data sheet or label.

4.2. Most important symptoms and effects, both acute and delayed Tissue

damaging effects: The product contains substances that are corrosive. If vapor or aerosols are inhaled, it can cause damage to the lungs and cause irritation and burning in the respiratory organs as well as coughing. Corrosive substances cause irreversible damage to the eyes. Corrosive to the skin.

4.3. Indication of immediate medical attention and special treatment needed Show this safety data sheet to doctor or emergency department.

SECTION 5: Fire fighting

5.1. Extinguishing media

Extinguish with powder, foam, carbonic acid or water mist.

Do not use a water jet as this can spread the fire.

5.2. Special hazards associated with the substance or mixture The

product is not immediately flammable. Avoid inhalation of vapors and fumes - seek fresh air.

In case of fire, dangerous flue gases are formed.

In case of fire, thick black smoke will be produced.

Exposure to decomposition products can cause health damage.



Safety data sheet

5.3. Instructions for firefighters Contaminated extinguishing water is sent for destruction. Extinguishing water that has been in contact with the product can be corrosive. If there is a risk of exposure to vapors and flue gases, a self-contained breathing apparatus must be worn.

SECTION 6: Precautions against accidental release

6.1. Personal safety measures, personal protective equipment and emergency procedures Use personal protective equipment - see section 8. Avoid inhalation and contact with skin and eyes.

6.2. Environmental protection measures Contact the authorities in connection with contamination of the soil and water environment and in the event of spillage into sewers. Spillage must not be discharged into sewers and/or surface water.

6.3. Methods and equipment for containment and cleaning Spills are contained and collected with sand or other absorbent material and transferred to suitable waste containers. Beware of the risk of corrosion.

6.4. Reference to other points See point 8 for type of protective equipment. See point 13 for disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling See under point 8 for information on precautions for use and personal protective equipment. The product should be used in well-ventilated conditions. There must be access to running water and eyewash. There may be additional requirements for ventilation and protective equipment, see executive order on work with code-numbered products.

7.2. Conditions for safe storage, including any incompatibility The product should be stored securely, out of the reach of children and not together with food, feed, medicines etc. Should be stored in tightly closed original packaging. Must be stored in a dry, cool and ventilated place.

7.3. Special uses See use section 1.

SECTION 8: Exposure controls/personal protective equipment

8.1. Control parameters

Limit values according to executive order no. 291 of 19/03/2024 on limit values for substances and materials (chemical agents) in the working environment:

Content Short-term	8-hour		Note
	limit value ppm / mg/m ³ - /	limit value ppm / mg/m ³ - / 2	
Sodium hydroxide	-	- / 2	L

L = The limit value is a ceiling value that must not be exceeded at any time.

DNEL/PNEC values:

DNEL Sodium hydroxide	Workers	Consumers
Inhalation - Chronic Local	1 mg/m ³	1 mg/m ³

8.2. Exposure controls There is no exposure scenario for this product.

Appropriate exposure control measures:

Use protective equipment as indicated below. Wash hands before breaks, toilet visits and after finishing work. Do not eat, drink or smoke while using this product.

Randers Kemiske Industri

Safety data sheet

Personal protective equipment:



Respiratory protection:

Usually not required.
Use respirator with A2/P2 filter in case of insufficient ventilation.

Protection of hands:

Use protective nitrile rubber gloves (>0.11 mm). Protective gloves must comply with EN 374.
Penetration time: > 240 min. (Class 5).

Eye/ face protection:

Use safety glasses or a face shield.

Protection of skin:

Special work clothes should be used.

Measures to limit environmental exposure:

It must be ensured that local regulations for discharge are observed.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Liquid
Color:	Colorless
Odor:	Characteristic
Melting point/Freezing point	5
(°C): Boiling point or initial boiling point and boiling range (°C): Flammability: Lower and upper explosion limit (vol-%): Flash point (°C): Autoignition temperature (°C): Decomposition temperature (°C): pH:	-
Kinematic viscosity	-
(mm ² /s): Solubility: Partition coefficient n-octanol/water (log value): Vapor pressure: Density and/or relative density: Relative vapor density: Particle properties:	-
	14
	-
	Soluble in water
	-
	-
	1,395
	-
	-

9.2. Other information

No.

SECTION 10: Stability and reactivity

10.1. Reactivity

May etch metals.

Reacts with water.

Dissolves grease deposits and attacks gaskets, certain plastics and rubber materials.

Reacts with metals to form hydrogen with the risk of forming explosive hydrogen/air mixtures.

10.2. Chemical stability

The product is stable when used according to the supplier's instructions.

10.3. Risk of dangerous reactions

None known.

10.4. Conditions to avoid

Avoid contact with moisture and water.

Avoid exposure to daylight or other light sources.

10.5. Materials to avoid

Avoid contact with metals.

Avoid contact with strong acids.



Safety data sheet

10.6. Hazardous decomposition products

None under recommended storage conditions.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) no. 1272/2008****Acute toxicity:**

The database does not give rise to classification.

Substance	Exposure route	Art	Testing	Result
No data.	-	-	-	-

Skin corrosion/irritation:

Has a corrosive effect and causes burning pain, redness, blisters and caustic wounds.

May cause corrosion in the mouth, esophagus and stomach. Pain in the mouth, throat and stomach. Difficulty swallowing, feeling sick and vomiting blood. Brown spots and caustic ulcers can be seen in and around the mouth.

Serious eye damage/eye irritation:

May cause deep burns, pain, tearing and spasms in the eyelids. Risk of serious eye damage with vision loss.

Respiratory sensitization or skin sensitization:

The database does not give rise to classification.

Germ cell mutagenicity:

The database does not give rise to classification.

Carcinogenicity:

The database does not give rise to classification.

Reproductive toxicity:

The database does not give rise to classification.

Single STOT exposure:

The database does not give rise to classification.

Repeated STOT exposures:

The database does not give rise to classification.

Aspiration hazard:

The database does not give rise to classification.

11.2. Information on other hazards

Test data not available.

SECTION 12: Environmental information**12.1. Toxicity**

Substance	Duration of the test	Art	Testing	Result
Sodium hydroxide	48 hours	Daphnia	EC50	40.4mg/L

12.2. Persistence and degradability Substance**Degradability in the aquatic environment**

Substance	Testing	Result
No data.	-	-

12.3. Bioaccumulative potential Substance**Potentially bioaccumulative**

Substance	LogPow
No data.	-

12.4. Mobility in soil

Test data not available.

12.5. Results of PBT and vPvB assessment

The product does not meet the criteria for PBT or vPvB.

12.6. Hormone-disrupting properties

Test data not available.



Safety data sheet

12.7. Other negative effects The product will locally change the pH in the aquatic environment.

SECTION 13: Disposal

13.1. Methods for waste treatment The product is covered by the regulations on hazardous waste. Spills and waste are collected in closed and tight containers, which are disposed of via the municipal waste scheme for hazardous waste with the specifications below.

EAK code	Description	Chemical waste group
06 02 04	Sodium and potassium hydroxide	X

Special marking:
-

Contaminated packaging:
Empty packaging and residues must be handed over to the municipal waste scheme for hazardous waste.

SECTION 14: Transport information

The product is covered by the conventions on dangerous goods.

14.1 - 14.4.

ADR

14.1. UN number or ID number 1824	14.2. UN proper shipping name	14.3. Transport hazard class(es)	14.4. Packaging group
	SODIUM HYDROXIDE SOLUTION	8	II

IMDG/IATA

14.1. UN number or ID number 1824	14.2. UN proper shipping name	14.3. Transport hazard class(es)	14.4. Packing group
	SODIUM HYDROXIDE SOLUTION	8	II

14.5. Environmental hazards
-

14.6. Special precautions for the user
-

14.7. Bulk transport by sea according to IMO instruments
Not relevant.

SECTION 15: Information on regulation

15.1. Special regulations/specific legislation for the substance or mixture with regard to safety, health and the environment

Sources:

The Norwegian Working Environment Authority's order no. 301 of 13 May 1993 on determining code numbers, with later amendments.

Order on work with substances and materials (chemical agents) - BEK no. 381 of 12/04/2023, with subsequent amendments.

The Norwegian Working Environment Authority's order no. 1049 of 30 May 2021 on youth work, with later amendments.

Executive order no. 1369 of 25 November 2015 on marketing and labeling of volatile organic compounds in certain paints and varnishes as well as products for car refinishing.

Executive order no. 1565 of 19 December 2022 on the import and sale of highly toxic and toxic substances and mixtures, etc., on the storage and reporting of theft of certain substances and mixtures and on the prohibition of misleading statements when marketing substances and mixtures.

Executive order no. 6 of 4 January 2023 of the Chemicals Act.

Executive order no. 1794 of 18/12/2015 on special duties for manufacturers, suppliers and importers etc. of substances and materials under the Act on the Working Environment, with subsequent amendments.

Executive order no. 291 of 19/03/2024 on limit values for substances and materials (chemical agents) in the working environment, with subsequent amendments.

Executive order no. 573 of 23/05/2024 on waste, with later amendments.

Other marking:

PR number: 4117127

MAL Code (1993):

00-4



Safety data sheet

Limitations of use:

Young people under the age of 18 may not professionally use or be exposed to the product. However, young people over the age of 15 are exempt from this rule if the product is included as a necessary part of an education. (cf., however, the Norwegian Working Environment Authority's Executive Order on youth work).

Requirements for special education:

—

15.2. Chemical Safety Assessment

No.

SECTION 16: Other information

Prepared on the basis of EU regulation 1907/2006 (REACH)

Other information:

Sources:

EU regulation no. 1907/2006 (REACH), with later adaptations.

EU regulation no. 1272/2008 (CLP), with later adaptations.

Directive 2008/98/EC

ECHA – The European Chemicals Agency.

The full wording of H sentences referred to in points 2+3:

H290 May corrode metals.

H314 Causes severe skin corrosion and eye damage.

H318 Causes serious eye damage.

Classification according to Regulation (EC) no. 1272/2008:

Skin Corr. 1A;H314 Calculation method

Eye Dam.1;H318 Calculation method

Abbreviations and acronyms used in the safety data sheet:

REACH: Registration, assessment and approval of and restrictions on chemicals. Regulation (EC) no. 1907/2006.

CLP: Regulation (EC) no. 1272/2008 on classification, labeling and packaging.

CAS No.: Chemical Abstracts Service number.

EC no.: EINECS and ELINCS number (see also EINECS and ELINCS).

DNEL: Derived No-Effect Level (Derived No-Effect Level).

PNEC: Predicted No Effect Concentration (Predicted No Effect Concentration).

STOT: Specific Target Organ Toxicity (Specific Target Organ Toxicity).

LD50: Lethal Dose for 50% of a test population.

LC50: Lethal concentration for 50% of a test population.

EC50: The effective substance concentration that causes 50% of the maximum response.

PBT: Persistent, Bioaccumulative and Toxic substance (Persistent, Bioaccumulative and Toxic).

vPvB: Very persistent and very bioaccumulative (Very Persistent and Very Bioaccumulative).

NOEC: The highest tested concentration where, in a study, no statistically significant effect is observed in the exposed population compared to an appropriate control group (No Observed Effect Concentration).

NOAEL: The highest tested dose or the highest tested exposure level at which no statistically significant increases in the frequency or severity of adverse effects occur between the exposed population and an appropriate control group. Some effects may occur at this level, but they are not considered harmful or precursors of harmful effects.

Other:

The information in this safety data sheet only applies to the product mentioned in point 1 and is not necessarily valid when used together with other products.

Changes have been made in the following points:

General update.

This safety data sheet replaces version:

1.8