

P / TYPE
COVERT SURVEILLANCE



The Argus[®] P-Type thermal imaging camera is specially designed to help police, security and law enforcement officers detect the heat signatures of people and objects.

The Argus[®] P-Type can be used in conditions of zero visibility including complete darkness and smoke. This is because the energy being sensed is heat rather than light allowing the camera to be used in both day and night operations and for many different applications.

The Argus[®] P-Type is a robust, self-contained, simple-to-operate thermal imaging camera with interchangeable lenses allowing the camera to be used effectively for differing operational distances. It is lightweight and ergonomic, capable of withstanding harsh environments and contains many of the most advanced features available for any thermal imaging camera.

The Argus[®] P-Type is available with either a 320 x 240 pixel or 160 x 120 pixel Amorphous Silicon (ASi) Microbolometer Detector. The camera has been designed using advanced digital imaging technology and techniques for superior performance and application specific functionality

TO BOOK A DEMONSTRATION OR FIND OUT MORE GO TO:

argusdirect.com

CAMERA STANDARD FEATURES

The Argus[®] P Type comes with the most advanced features available in any Thermal Imaging Camera. **These include:**

Interchangeable Lenses	Choice of Colour Modes additional colour modes optionally available
Shuttered OLED Display	Customisable Start-up Screen
Digital Image Capture 1000 images (option)	Time and Date
Digital Video Capture (option)	Digital Zoom
Image/Video Replay (option)	On Screen Set-up Menu
Fast 5 second power-up. standby mode not required	
Up to 5 hours Battery Life	

CAMERA STANDARD ACCESSORIES

The Argus[®] P Type comes with the following accessories as standard:

Quick Start Guide	Video Output Cable
User Manual	4GB Memory Card
Rechargeable Battery Pack	USB Cable
Mains Charger	Neck Strap
In-Car Charging Cable	Lens Cloth

CAMERA OPTIONAL ACCESSORIES

Security Application Colour Modes - ARG_TTP_AM_F	Image and Video Capture - ARG_TTP_IV
Sport Application Colour Modes - ARG_TTP_AM_S	Black Hard Case - ARG_P_BHC
Specialist Application Colour Modes - ARG_TTP_AM_SS	Argus Soft Case - ARG_TTP_SC
Marine Application Colour Modes - ARG_TTP_AM_M	Additional Li-ion battery - ARG_TTP_BP
	Please refer to the Argus website for details.

CAMERA ORDER CODES

Code	Resolution	Frame rate
PB160	160x120	30Hz
PB169	160x120	9Hz
PB320	320x240	30Hz
PB329	320x240	9Hz

LENSES

Code (order separately)

ARG_PLENSB
ARG_PLENSC
ARG_PLENSD
ARG_PLENS E
ARG_PLENSF

PERFORMANCE

Lens	Field of View (Horizontal) 160 x 120 sensor	Field of View (Horizontal) 320 x 240 sensor	
B	26°	50°	Identification approx 24m Recognition approx 90m Detection approx 230m
C	12°	24°	Identification approx 50m Recognition approx 190m Detection approx 500m
D	6.5°	13°	Identification approx 90m Recognition approx 350m Detection approx 950m
E	5°	10°	Identification approx 115m Recognition approx 460m Detection approx 1250m
F	3.5°	7°	Identification approx 165m Recognition approx 650m Detection approx 1750m

Note: Identification as friend or foe at 6.25cm/pixel. Recognition as person / object at 25cm/pixel. Detection of person at 66.7cm/pixel.

OPTICAL DATA

Detector

Sensor type	Un-cooled Microbolometer
Sensor material	Amorphous Silicon (ASi)
Resolution	384 x 288 array (320 x 240) used or 160 x 120
Pixel size	25µ
Spectral response	8 – 14µm
MDTD	<100 mK typical (Minimum Discernible Temperature Difference)
Dynamic range	-40°C to 150° (-40°F to 300°F)
Refresh rate	60Hz (PB320), 120 Hz (PB160)

Lens

Lens material	Germanium				
Type	B	C	D	E	F
Focal length	8.6	19	35	46	65
Aperture	f/1.0	f/1.3	f/1.2	f/1.0	f/1.3
Horz. Field of view PB160	26°	12°	6.5°	5°	3.5°
Horz. Field of view PB320	50°	24°	13°	10°	7°

Image Presentation

Type	OLED Microdisplay
Pixel format	QVGA 320 x 240 x RGB
Pixel count	320 x 240 x 3 = 230,400 Pixels
Diopter adjustment	+2 to -4
Standard Colour Modes	White hot, Black hot
Update rate	PB160/320 30fps; PB169/329 9fps
Image Capture	JPEG or RAW format, 1000 images
Video Capture	AVI (MJPEG) format, approx 0.2GB/hr PB160/320 10fps; PB169/329 9fps

ELECTRICAL DATA

Interfaces

Power	12VDC for use with supplied mains or vehicle adaptor leads
Computer	Mini-USB (USB2) (USB Mass Storage Device)
Video Output	NTSC 525 line 60 Hz, EIA RS-170 PB160/320 30 fps; PB169/329 9 fps
Memory Card	Compatible with MicroSD
Power Power Consumption	3W typical
Start-up time	5 seconds typical
Battery type	Li-ion (DR5)
Battery life	Up to 5 hours
Battery recharge time	4 hours approx in camera 3 hours approx in charger
Charging temp.	0°C to 40°C (32°F to 104°F)
Alternative Battery (option)	Lithium AA FR6 Primary x 4
Lithium AA Battery Life	Up to 5 hours
External power/charging	100 - 240 VAC 50/60Hz or 12VDC (with vehicle adaptor)

MECHANICAL DATA

Camera dims (H x W x D)	232mm x 93mm x 77mm With B or C lens and cover fitted. Excludes removeable eyecup and straps
Camera weight	<0.95 kg (<2.1 lb) including battery, B or C lens, straps and cover.

ENVIRONMENTAL DATA

Operating Temperature	-20°C to +60°C (-4°F to 140°F)
Long term storage	-20°C to +60°C (camera) -10°C to +50°C (Li-ion battery)
Sealing	Waterproof (IP65)*
Vibration/Shock	EN 60721-3-2 Class 2M3
EMC Emissions	BS EN & AS/NZ 61000-6-3:2007 EN 50489:2010 FCC CFR 47 PART 15b:2010 ICES-003(2004) (Canada)
EMC Immunity	BS EN 61000-6-2:2005 EN 50498:2010
RoHS	Compliant
Safety	IEC 60950-1 and related national standards

* Connector cover fitted lens fitted and battery cover closed.

WARRANTY

24-month warranty as standard.
Warranty can be extended for up to an additional three years at the time of purchase (exclusions apply).

Whilst e2v technologies has taken care to ensure the accuracy of the information contained herein it accepts no responsibility for the consequences of any use thereof and also reserves the right to change the specification of goods without notice. e2v technologies accepts no liability beyond the set out in its standard conditions of sale in respect of infringement of third party patents arising from the use of tubes or other devices in accordance with information contained herein.

e2v technologies (uk) limited, Waterhouse Lane, Chelmsford, Essex CM1 2QU United Kingdom
Holding Company: e2v technologies plc Telephone: +44 (0)1245 493493 Facsimile:
+44 (0)1245 492492 Contact e2v by e-mail: enquiries@e2v.com or visit www.e2v.com
for global sales and operations centres. © e2v technologies (uk) limited 2013