

## Argus® P-Type: Interchangeable Lens (Lens C) - ARG\_PLENSC

### Introduction

Lens C is a manual focus lens giving a wide field of view of 24° when used on a P320 camera model, and a medium field of view of 12° on a P160 camera.

The lens simply attaches to the front of the camera on a bayonet fitting; the camera has a quick release push button to release the lens.

The front element has a hard carbon coating and the lens is sealed to IP67

Supplied boxed and in a black bottle case with front lens cap & lanyard and a rear cover.

Further data on range performance and details of other lenses are given on the P-type camera datasheet



### Physical Data

- Length: 31mm overall  
24 mm external to camera
- Diameter: 62mm
- Weight: 140g
- Operating Temperature: -20°C to +60°C
- Coating Durability: MIL-C-48497 4.5.3.1/2/3  
BS EN 6006/8-2-52 Kb Salt Mist Severity 2

### Optical Data

- Focal Length: 19mm
- Aperture: f/1.3
- Focus: Manual 0.5m - infinity
- Horizontal Field of View (P160): 12°
- Horizontal Field of View (P320): 24°
- Camera MDTD with this lens: 85mK typical
- Typical detection of man-sized object: 500m (0.66m / pixel)
- Horizontal Field of view at 200m (P160): 43m
- Horizontal Field of view at 200m (P320): 88m

Whilst e2v technologies has taken care to ensure the accuracy of the information contained herein it accepts no responsibility for the consequences of any use thereof and also reserves the right to change the specification of goods without notice. e2v technologies accepts no liability beyond the set out in its standard conditions of sale in respect of infringement of third party patents arising from the use of tubes or other devices in accordance with information contained herein.

e2v technologies (uk) limited, Waterhouse Lane, Chelmsford, Essex CM1 2QU United Kingdom Holding Company: e2v technologies plc Telephone: +44 (0)1245 493493 Facsimile: +44 (0)1245 492492

Contact e2v by e-mail: [enquiries@e2v.com](mailto:enquiries@e2v.com) or visit [www.e2v.com](http://www.e2v.com) for global sales and operations centres.

© e2v technologies (uk) limited 2013