


Leclanché Capacitors  
48, av. de Grandson  
1400 Yverdon, Switzerland



Tel. +41 24 445 66 88  
Fax +41 24 445 66 89  
[capinfo@Lcap.ch](mailto:capinfo@Lcap.ch)  
[www.Lcap.ch](http://www.Lcap.ch)

Drawing No. : 100011225  
created from : hm 10/06/2013 13:56:00

**Part Number : AG10101610020**



Ø D : 10 mm  
L : 20 mm  
l : 40 mm  
d : 0,8 mm

Terminals : Wire

**Electrical Parameter**

Rated Capacitance ( C <sub>R</sub> ) @ 100 Hz / 20 °C	<b>100</b> µF	
Tolerance	<b>-10 / +50</b> %	
Rated Voltage ( U <sub>R</sub> )	<b>16</b> V	
Surge Voltage ( U <sub>S</sub> ) max. 5 x 1 min / h	<b>18</b> V	
Reverse Voltage ( U <sub>U</sub> ) max. 1 s	<b>2</b> V	
Leakage Current ( I <sub>L</sub> ) @ U <sub>R</sub> / 5 min / 20 °C	<b>14</b> µA	
ESR typ. @ 100 Hz / 20°C	<b>960</b> mΩ	
Tan δ typ. @ 100 Hz / 20°C	<b>6</b> %	
Z max. @ 10 kHz / 20°C	<b>860</b> mΩ	
ESL typ.	<b>20</b> nH	
Rated Ripple Current ( I <sub>R</sub> ) @ 100 Hz / 85 °C	<b>0,28</b> A	
Useful life @ I <sub>R</sub> , U <sub>R</sub> , 85 °C	<b>14000</b> h	
IEC Climatic category / Standards	<b>55/085/56</b>	<b>IEC 60384-4</b>
Applications	General Industrial	
Your article No. / Project		