


#5774

Discharge CAPACITORS

PPMF 100-50.0 cv5 J

Preliminary
data sheetDielectric of metallized
polypropylene

Threaded outputs

Resin end sealing

Aluminium case

Parameter	Symbol	Value	Unit	Condition
Capacitance	C	50	μF	1 V / 1 kHz
Tolerance		± 5	%	
Rated voltage	Un DC	1000	VDC	
RMS Current permanent	I _{eff max.}	35	A _{eff}	2 kHz to 10 kHz
Repetitive surge current	I _{cr. max.}	700	A	
Equivalent serie resistance	ESR	4.5	m Ω	1 V / 10 kHz
Stray inductance	ESL	≤ 80	nH	
Insulation resistance	R _i x C	$\geq 30'000$	s	300 VDC - 1 min
Test voltage between terminals	U T1	1600	VDC	10 s
Test voltage terminals to case	U T2	2500	VAC	50 Hz / 1 min
Operating temperature		-10 / + 50	$^{\circ}\text{C}$	
Estimated operational life (-5 %)		$> 5 \times 10^9$	Discharges	1000 V / 700 A

Dimension	Symbol	Value	Unit	Conditions
Diameter	D	65	mm	
Height	H	120	mm	
Terminals				
Thread		M6 x 12	mm	
Thread spacing	e	22	mm	
Fixing stud		M12 x 16	mm	
	M1			
	M0			
	Modification	Date	Visa émetteur	

Condensateurs
Kondensatoren
CapacitorsCH 1400 Yverdon-les-Bains
Tel.: ++41 24 447 22 82
Fax: ++41 24 447 22 85

Le lanché
Capacitors
AFFISCHER & FANSCHE COMPANY

HJJ

02.12.2008

faisab5774.XLS