



Construction:

The Delta RFI capacitors consist of the winding units of the C 303 and C 333 capacitors, which are with international CB - certificates certified. Tubular plastic case with epoxy resin sealed Flame retardand (UL 94V-0)

Leads: stranded wire

Capacitor complies: IEC 60384-14/93

Climatic category:
 40/085/56 (IEC 60068-1)

Temperature range: -40°C ÷ +85°C

Nominal working voltage: 250 V, 50 Hz

Insulation resistance between the leads:
 > 30 GΩ
 Insulation resistance between leads and the case > 100 GΩ

Test voltage between X2 capacitor leads:
 1500 VDC, 60 sec.

Test voltage between Y2 capacitor leads:
 3000 VDC

Test voltage between all leads and case:
 2000 V, 50 Hz 60 sec.

Type	C1		C2, C3,		dimensions [mm]			Current [Aef]	Leads - stranded wire [mm²]
	[µF]	Class	[nF]	Class	D	L	Lv/Lvo		
RFI	0,1	X2	2 x 2,5	Y2	18	24	100**	6,3	0,5
	0,22	X2	2 x 2,5	Y2	20	36	100**	6,3	0,5
	0,33	X2	2 x 2,5*	Y2	20	36	100**	6,3	0,5

*Other values of capacity on request

**Other lengths of leads on request

