


Leclanché Capacitors
48, av. de Grandson
1400 Yverdon, Switzerland



Tel. +41 24 445 66 88
Fax +41 24 445 66 89
capinfo@Lcap.ch
www.Lcap.ch

Drawing No. : 100011226
created from : hm 10/06/2013 14:19:00

Part Number : AG22202521036



Ø D : 21 mm
L : 36 mm
l : 40 mm
d : 0,8 mm

Terminals : Wire

Electrical Parameter

Rated Capacitance (C_R) @ 100 Hz / 20 °C	2200 μ F	
Tolerance	-10 / +50 %	
Rated Voltage (U_R)	25 V	
Surge Voltage (U_S) max. 5 x 1 min / h	29 V	
Reverse Voltage (U_U) max. 1 s	2 V	
Leakage Current (I_L) @ U_R / 5 min / 20 °C	170 μ A	
ESR typ. @ 100 Hz / 20°C	43 m Ω	
Tan δ typ. @ 100 Hz / 20°C	6 %	
Z max. @ 10 kHz / 20°C	52 m Ω	
ESL typ.	20 nH	
Rated Ripple Current (I_R) @ 100 Hz / 125 °C	2,1 A	
Useful life @ $I_R, U_R, 125$ °C	5000 h	
IEC Climatic category / Standards	55/125/56	IEC 60384-4
Applications	General Industrial	
Your article No. / Project		