


Leclanché Capacitors
48, av. de Grandson
1400 Yverdon, Switzerland



Tel. +41 24 445 66 88
Fax +41 24 445 66 89
capinfo@Lcap.ch
www.Lcap.ch

Drawing No. : 1027178-53567
created from : 29/04/2014 16:41:00

Part Number : AG68106316030



Ø D : 16 mm
L : 30 mm
l : 40 mm
d : 0,8 mm

Terminals : Wire

Electrical Parameter

Rated Capacitance (C_R) @ 100 Hz / 20 °C	680 μ F	
Tolerance	± 20 %	
Rated Voltage (U_R)	63 V	
Surge Voltage (U_S) max. 5 x 1 min / h	72 V	
Reverse Voltage (U_U) max. 1 s	2 V	
Leakage Current (I_L) @ U_R / 5 min / 20 °C	180 μ A	
ESR typ. @ 100 Hz / 20°C	117 m Ω	
Tan δ typ. @ 100 Hz / 20°C	5 %	
Z max. @ 10 kHz / 20°C	94 m Ω	
ESL typ.	20 nH	
Rated Ripple Current (I_R) @ 100 Hz / 105 °C	1,6 A	2 A @ 300 Hz
Useful life @ $I_R, U_R, 105$ °C	32000 h	
IEC Climatic category / Standards	55/105/56	IEC 60384-4
Applications	General Industrial	
Your article No. / Project		