

Leclanché Capacitors
48, av. de Grandson
1400 Yverdon, Switzerland



Tel. +41 24 445 66 88
Fax +41 24 445 66 89
capinfo@Lcap.ch
www.Lcap.ch

Drawing No. : 1024347-53567
created from : 01/11/2012 14:11:00

Part Number : GSH22204025035

	<p>∅ D : 25 mm L : 35 mm</p>	
<p>Insulation : PVC 2500 Vac</p> <p>Terminals : DIN</p>		

Electrical Parameter

Rated Capacitance (C_R) @ 100 Hz / 20 °C	2200 μ F	
Tolerance	±20 %	
Rated Voltage (U_R)	40 V	
Surge Voltage (U_S) max. 5 x 1 min / h	46 V	
Reverse Voltage (U_U) max. 1 s	2 V	
Leakage Current (I_L) @ U_R / 5 min / 20 °C	528 μ A	
ESR typ. @ 100 Hz / 20°C	72 m Ω	
Tan δ typ. @ 100 Hz / 20°C	10 %	
Z max. @ 10 kHz / 20°C	70 m Ω	
ESL typ.	20 nH	
Rated Ripple Current (I_R) @ 100 Hz / 105°C	1,6 A	
Useful life @ I_R , U_R , 105°C	5000 h	
IEC Climatic category / Standards	40/105/56	IEC 60384-4
Applications	General Industrial	
Your article No. / Project		