


#6186

Security Capacitors


CKT 501-4BDF 16-047 K



According to NFF 62-102

Dielectric of metallized polyester

Polyester wrapped UL510 / Epoxy resin sealing UL 94-V0



Parameter	Symbol	Value	Unit	Condition
Capacitance	C	0.47	μF	1 V / 1 kHz
Tolerance		± 10	%	
Rated voltage	Un DC	160	VDC	
Rated voltage	Un AC	100	Veff	50 Hz / 85°C
Tangente delta	tgδ	< 70	1C ⁴	1 kHz
Insulation resistance	Ri	> 21'300	MΩ	100 VDC - 1 min
Test voltage between terminals	U T1	256	VDC	10 s
Operating temperature		- 55 / + 125 °C		

Dimension	Symbol	Value	Unit	Conditions
Width	B max	13.5	mm	
Height	H max	10	mm	
Length	L max	21	mm	
Terminals				
Radial tinned wire	d	0.8	mm	
RM		5.08 ± 1.0	mm	
Lenght	i	> 25 mm		

M1			
M0			
Modification	Date	Visa émetteur	

Condensateurs CH 1401 Yverdon-les-Bains
 Kondensatoren Tel.: ++41 24 445 66 88
 Capacitors Fax: ++41 24 445 66 89



HJJ

24.05.2013

faisab6186.XLS