


#5959

Plastic Film Capacitors

MKS 4-010 g F



Self-extinguishing plastic housing

Dielectric metallized polyphenylene sulfide - Epoxy resin sealing UL 94-V0

Parameter	Symbol	Value	Unit	Condition
Capacitance	C	0.1	μF	1 V / 1 kHz
Tolerance		± 1	%	
Rated voltage	Un DC	40	VDC	85°C
Rated voltage	Un AC	20	VAC	50 Hz
Rated temperature		85	°C	
RMS current	I RMS max.	1	A _{eff}	100 kHz
slope of voltage variation	du/dt max.	12	V/μsec	max. repetitive
Repetitive surge current	I cr. max	1.2	A	
Tangent delta	tgδ	≤ 15	10 ⁻⁴	1 kHz / 23°C
Tangent delta	tgδ	≤ 25	10 ⁻⁴	10 kHz / 23°C
Stray inductance	ESL	≤ 30	nH	
Insulation resistance	Ri	> 15'000	MΩ	40 VDC - 1 min
Test voltage between terminals	U T1	64	VDC	10 s
Climatic category		55/125/21		
Dimension	Symbol	Value	Unit	Conditions
Width	B max	3.5	mm	
Height	H max	7	mm	
Length	L max	8	mm	
Terminals				
Axial tinned wire	d	ø 0.6 x 20	mm	
	RM	5.0 ± 0.5	mm	
	M1			
	M0			
	Modification	Date	Visa émetteur	

Condensateurs CH 1400 Yverdon, Switzerland
 Kondensatoren Tel.: ++41 24 445 66 88
 Capacitors Fax: ++41 24 445 66 89

Leclanché
Capacitors
A FRICKER & TELESCHE COMPANY

HJJ

www.Lcap.ch
 13.09..2010

capinfo@Lcap.ch
 faisab5959.XLS