



#5639

HIGH TEMPERATURE FILM CAPACITORS



MKS-4 50-5.6 nr K



Printed circuit board mounting

Dielectric of

metallized polyphenylene sulfide



Parameter	Symbol		Value	Unit	Condition
Capacitance	C		5.6	μF	1 V / 1 kHz
Tolerance			± 10	%	
Rated voltage	Un DC		500	VDC	
Rated voltage	Un AC		250	Veff	50 Hz
RMS current	I RMS max.		6.5	Aeff	10 kHz / 110 °C
slope of voltage variation	du/dt max.		40	V/μsec	max. repetitive
Repetitive surge current	I cr. max		224	A	
Tangente delta	tgδ		≤ 6	10 ⁻⁴	1 V / 1 kHz
Tangente delta	tgδ		≤ 18	10 ⁻⁴	1 V / 10 kHz
Stray inductance	ESL		≤ 50	nH	
Insulation resistance	Ri		> 1'000	MΩ	100 VDC - 1 min
Test voltage between terminals	U T1		800	VDC	10 s
Operating temperature			- 55 ... + 125	°C	
Dimension	Symbol			Unit	Conditions
Diameter	D		37	mm	
Terminals tinned wire (4 x)	ø d		1.2	mm	
RM1			40	mm	
RM2			25	mm	
	M1				
	M0				
	Modification	Date	Visa émetteur		

Condensateurs
Kondensatoren
Capacitors

CH 1400 Yverdon-les-Bains
Tel.: ++41 24 445 66 88
Fax: ++41 24 445 66 89

Le laniché
Capacitors
A FISCHER & TAUERSCHE COMPANY

HJJ

14.02.2007

faisab5639.XLS