



Document Number V00\_170322

# Product specification

LSUM 162R4L 0015F EA



# Product specification

## ■ Specification

### 1. Primary specification

Part number	Capacitance (F)	Max. ESR (mΩ) <sub>DC</sub>	Max. Current (A) Non-repeated (Calculated value)	Leakage Current (mA)
LSUM 162R4L 0015F EA	15.5	110	460	< 32

### 2. Power & Energy

Part number	Usable Specific Power, $P_d$ (W/kg) <sup>1</sup>	Impedance Match Specific Power, $P_{max}$ (W/kg) <sup>2</sup>	Energy Density (Wh/kg)	Max. Stored Energy (Wh)
LSUM 162R4L 0015F EA	1,500	3,200	3.0	56.7

### 3. Standard & Reliability

Rated Voltage	162.4V		
Max. Voltage <sup>3</sup>	174V		
Maximum Series Voltage	750V		
Capacitance Tolerance	0% / +20%		
Operating temperature range	-40 ~ 65 °C		
Storage temperature range	-40 ~ 70 °C		
Max. continuous current <sup>4</sup>	$\Delta T = 15$ °C	7A	
	$\Delta T = 40$ °C	12A	
Endurance Life (65 °C)	1,500 Hours		
	Capacitance change	Within 20% of initially specified value	
	ESR change	Within 100% of initially specified value	
Projected Life Time (25 °C)	10 Years at rated voltage		
	Capacitance change	Within 20% of initially specified value	
	ESR change	Within 100% of initially specified value	
Projected Cycle Life (25 °C) <sup>5</sup>	500,000 Cycles		
	Capacitance change	Within 20% of initially specified value	
	ESR change	Within 100% of initially specified value	
Shelf Life (25 °C)	4 Years stored uncharged state		

### 4. Monitoring

Part number	Temperature sensor	Temperature & Voltage interface	Connector	Cell voltage monitoring	Balancing
LSUM 162R4L 0015F EA	PTC	Alarm	Molex 5559-08P	Over voltage alarm	Passive

#### \*Remarks

1) Usable specific power

$$P_d = \frac{0.12 \times V^2}{ESR \times mass}$$

2) Impedance match specific power

$$P_{max} = \frac{V^2}{4 \times ESR \times mass}$$

3) Non repeated, not to exceed 1sec.

4) Initial state value.

5) Actual cycle value can be subject to various application conditions.

# Product specification

## Safety & Physical Protection

Part number	Isolation voltage (DC)	Short circuit current(A)	Power Terminals	Recommended Torque - Terminal
LSUM 162R4L 0015F EA	2.5KV	1,400	M6	6 Nm

Dimension in mm (not to scale)

## Geometric properties

Part number	Dimension (mm)			Max. Weight (kg)
	Length	Width	Height	
LSUM 162R4L 0015F EA	684±2	202±1	183.5±1	18.5

