

### FEATURES

- Small size and low resistance
- Passive linear voltage balanced cells
- Quick charge and discharge
- JST ZHR-2 quick connect
- RoHS compliant
- UL recognized



### APPLICATIONS


- Pulse power demand
- Hybrid battery packs
- Portable electronic devices

### GENERAL SPECIFICATIONS

Item	Performance
Operating temperature	-40°C to +65°C @ 5.4V -40°C to +85°C @ 4.6V
Storage temperature	-40°C to +70°C
Capacitance	3F
Rated voltage	5.4 VDC / 4.6 VDC
Surge voltage	5.7 VDC
Temperature characteristics	Capacitance change: Within $\pm 5\%$ of initial measured value at +25°C (-40°C to +65°C) Internal resistance: Within $\pm 50\%$ of initial measured value at +25°C (at -40°C)
Endurance (At rated voltage & max. operating temp)	After 1000 hours: Capacitance change: within $\pm 30\%$ of initial rated value Internal resistance: Within 2 times of initial specified value
Projected Load life (At rated voltage & 25°C)	After 10 years: Capacitance change: Within $\pm 30\%$ of initial rated value Internal resistance: Within 2 times of initial specified value
Projected cycle life (From rated voltage to 1/2 rated voltage at 25°C)	After 500,000 cycles: Capacitance change: Within $\pm 30\%$ of initial rated value Internal resistance: Within 2 times of initial specified value
Shelf life	After 2 years at 25°C without load, the capacitor shall meet the specified endurance limits.

**DIMENSIONS**

Units = mm



**STANDARD PRODUCTS**

Part Number	Nom. Cap. (F)	GMV (F)*	ESR DC (mΩ)	ESR AC (mΩ) (1 KHz)	Leakage Current (mA) (72 hrs @ 25C)	Dimensions (mm)			Rated Current (A)
						L	W	T	
PBLL-3.0/5.4	3	2.7	325	205	0.19	25	22	12	4.1

\*NOTE: GMV = Guaranteed Minimum Value.