


## URKIRAPID J-15

Q/D Synthetic Enamel J-15 Satin Black



### DESCRIPTION



Quick-drying enamel for indoor and outdoor use. It stands out for its high coverage, good body, quick drying and satin appearance.

It is ideal for painting bodywork parts, metal work and machinery in general.

### COLORS



URKIRAPID

J-15 SATIN BLACK

### SURFACE PREPARATION



On steel: The surfaces to be painted must be properly derusted and degreased.

For a better adhesion and protection of the support, it can be previously primed with F-29 or F-809

On old paint, sand and degrease previously.

## APPLICATION



|                                                                                                                          |                                 |
|--------------------------------------------------------------------------------------------------------------------------|---------------------------------|
|  Application<br>viscosity<br>Dilution % | 20-25"<br>URKISOL 300<br>20-25% |
|  Gravity Gun<br>Application pressure    | 1,3-1,5 mm<br>3-4 bar           |
|  Number of coats<br>Total thickness     | 2 coats<br>30-40 µm             |
|  Flash time                             | 5-10'                           |
|  Drying Time<br>20°C                  | 30'                             |
|  %Gloss 60°- 60°                      | 10-15                           |

Can be repainted after 24 hours.

---

**SAFETY INSTRUCTIONS**

The use of appropriate personal protective equipment is recommended during application, to prevent the irritation of the respiratory tract, skin and eyes. For professional use only.

---

**STORAGE**

Keep in a tightly covered container, in a dry and ventilated place, avoiding direct exposure to sunlight. Temperature above 5°C is recommended, between 15 and 30°C optimal.

---

**VOC**

The VOC content of URKIRAPID J-15 is a maximum of 522 g/l.

---

The information contained in this Technical Specification Sheet is based on the knowledge and experience of the BESA technical department, and with it it's intended to advice and inform, being the responsibility of the user to take the necessary measures to guarantee the intended purpose of the product. **FOR PROFESSIONAL USE ONLY.**

---