


SPRAY URKI**PROTEC**

Repaintable Anti-Stone Chip



DESCRIPTION



SPRAY URKI**PROTEC** is a stone-chip protector with a satin aspect and rubber nature that provides a hard, strong and long lasting coat. It is designed to reproduce the manufacturer's original finish and provide protection against gravel, salt, moisture and rust and even absorb engine noise and vibration.

It is recoatable with most paint systems. As a precaution, apply a thin coat beforehand to avoid the creation of boils, bubbles, etc.

COLORS



URKI**PROTEC**

9005

SURFACE PREPARATION



Surfaces must be clean, dry and exempt of dust, grease and rust. For better adhesion of the product, peeling parts, dirt and rust must be removed.

USE



Shake the can for 2-3 minutes before using SPRAY URKI**PROTEC**. Apply 2-3 cross coats. After use, invert the can and clean the cap.

APPLICATION

 Shake can	2-3'
 Painting distance	20-30 cm
 Number of coats Total thickness	2-3 cross coats 150 µm
 Flash time	5-10'
 Drying Time 20°C 60°C	60' 30'

Can be repainted after 2 hours.

SAFETY INSTRUCTIONS

The use of appropriate personal protective equipment is recommended during application, to prevent the irritation of the respiratory tract, skin and eyes. For professional use only.

STORAGE

Keep in a tightly covered container, in a dry and ventilated place, avoiding direct exposure to sunlight. Temperature above 5°C is recommended, between 15 and 30°C optimal.

CAUTION: Under no circumstances should the packaging exceed 50°C.

VOC

The VOC content of SPRAY URKI**PROTEC** is a maximum of 840 g/l in compliance with European regulation 2004/42/EC IIB(E) (840) <840 g/l.

The information contained in this Technical Specification Sheet is based on the knowledge and experience of the BESA technical department, and with it it's intended to advice and inform, being the responsibility of the user to take the necessary measures to guarantee the intended purpose of the product. **FOR PROFESSIONAL USE ONLY.**